

This document was generated on 07/26/2017

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0015922060

Status: Active
Overview: EBBI™ 50D

Description: 1.27mm Pitch EBBI™ 50D Plug, Vertical, without Latch, 60 Circuits, 3.40mm PC Tail

Length

Documents:

3D Model RoHS Certificate of Compliance (PDF)

Drawing (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series <u>71661</u>

Application Board-to-Board, Signal, Wire-to-Board

Overview EBBITM 50D
Product Name EBBITM

POOTE 430774

UPC 800754397711

Physical

Breakaway Nο Circuits (Loaded) 60 Circuits (maximum) 60 Color - Resin Black Durability (mating cycles max) 2000 First Mate / Last Break No Flammability 94V-0 Glow-Wire Compliant Nο **Guide to Mating Part** No Keying to Mating Part None Lock to Mating Part None Material - Metal Copper Alloy

Material - Plating Mating Gold Material - Plating Termination Tin


Material - Resin High Temperature Thermoplastic

Net Weight 3.670/g Number of Rows 2 Orientation Vertical PC Tail Length 3.40mm **PCB** Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 1.60mm Packaging Type Tray Pitch - Mating Interface 1.27mm Pitch - Termination Interface 1.27mm Plating min - Mating 0.762µm 1.905µm

Plating min - Mating
Plating min - Termination
Polarized to Mating Part
Polarized to PCB
Shrouded
Stackable
Surface Mount Compatible (SMC)

0.702
Yes
Polarized to PCB
Yes
No

Temperature Range - Operating -40°C to +105°C Termination Interface: Style Through Hole



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -ED/01/2017 (12 January 2017) Halogen-Free

Status

Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

71661 Series

Mates With

EBBI™ 50D Receptacle <u>71660</u>, <u>87552</u>

Electrical

Current - Maximum per Contact 1.0A Voltage - Maximum 30V

Material Info

Engineering Number 716611060

Reference - Drawing Numbers

Sales Drawing SDA-71661-1***

This document was generated on 07/26/2017

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION