

## This document was generated on 02/23/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:			
	<u>033000003</u>		
Status:	Active		
Overview:	verview: MX150 Sealed and Unsealed Connector System		
Description:		t-Sealed or Unsealed Connectors, Tin Plating, 22 AWG,	- The second sec
Decemption	Right Reel Payoff		
	Right Reel Fuyer		
Decumenter			
Documents:		Deckering Specification 212025040,000 (DDF)	
Drawing (PDF)		Packaging Specification 313025040-000 (PDF)	
Product Specification PS-33012-002-001 (PDF)		Test Summary TS-33000-001-001 (PDF)	
	ation AS-33000-001-001 (PDF)	Datasheet (PDF)	Outin transmission Defension and
Application Specification AS-33000-001-CH-001		RoHS Certificate of Compliance (PDF)	Series image - Reference only
(PDF)			
Application Specification AS-33000-001-FR-001			EU ELV
(PDF)			Compliant
General			EU RoHS China RoHS
Product Family		Crimp Terminals	Compliant
Series		33000	REACH SVHC
Application		Power, Wire-to-Board, Wire-to-Wire	Not Contained Per -
Comments		For automatic and semi-automatic crimping, use Left	D(2021)10043-DC (17
		Reel Payoff terminals. See Sales Drawing for Left Reel	Jan 2022)
		Payoff Part Numbers.	Halogen-Free
Crimp Quality Equipment		Yes	<u>Status</u>
Overview		MX150 Sealed and Unsealed Connector System	Low-Halogen
Product Name		MX150	For more information, please visit <u>Contact US</u>
UPC		800756103549	
			China ROHS Green Image
Physical			ELV Compliant
Gender		Male	RoHS Phthalates Not Contained
Grip Code		22	
Material - Metal		High Performance Alloy (HPA)	
Material - Plating Mating		Tin	Search Parts in this Series
Material - Plating Termination		Tin	<u>33000</u> Series
Net Weight		0.290/g	
Packaging Type		Reel	Use With
Plating min - Mating		0.508µm	<u>33482</u> Dual Row Housing, <u>33481</u> Single
Plating min - Termination		0.508µm	Row Housing, 33486 Hybrid Housing
Termination Interface: Style		Crimp or Compression	
Wire Insulation Diameter		1.65mm max.	Annitestion Testing   EAO
Wire Size AWG		22	Application Tooling   FAQ
Wire Size mm <sup>2</sup>		0.50	Tooling specifications and manuals are
Electrical			found by selecting the products below.
Current - Maximum per Contact		Contact Molex	Crimp Height Specifications are then
Voltage - Maximum		14V DC	contained in the Application Tooling
			Specification document.
Solder Process Data			Global
Lead-freeProcess Ca	apability	N/A	Description Product #
			Extraction Toolkit for 2002220700
Material Info			MX150 Connectors PremiumGrade <u>638112600</u>
Reference - Drawing Numbers Application Specification			Hand Crimp
		AS-33000-001-001, AS-33000-001-CH-001,	Tool for 1.50mm
		AS-33000-001-FR-001	MX150 Blade Male
Packaging Specifica	tion	313025040-000	
Product Specification		PS-33012-002-001	Terminals, 18-22
Sales Drawing		SD-33000-001-001	AWG Extraction Tool for 638131500
Test Summary		TS-33000-001-001	
			MX150L, MX150, PT

This document was generated on 02/23/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION