

## This document was generated on 02/07/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status:	<u>0523163619</u> Active		
Description:	1.27mm Pitch Wire-to-Board Shielded Plug, Dual Row, IDT, 36 Circuits		
Documents: <u>3D Model</u> Drawing (PDF)		Product Specification PS-52986-017-001 (PDF) Packaging Specification SPK-52316-001-001 (PDF)	
Product Specificatio	n PS-52316-003 (PDF) n PS-52515-002 (PDF)	RoHS Certificate of Compliance (PDF)	
Agency Certification	n		- Series image - Reference only
UL		E29179	
General			EU ELV Not Relevant
Product Family		I/O Connectors	Not Relevant
Series		52316	EU RoHS China RoHS
Application		Wire-to-Board	Compliant
Comments		Conforms-IEEE 1284C Standard, Conforms-IEEE	REACH SVHC
		1284C Standard	Not Contained Per -
Component Type		Plug	ED/61/2018 (27 June
Product Name		Leaf Style Contact	2018)
Туре		N/A	Halogen-Free
UPC		822348198450	Status
			Not Low-Halogen
Physical			For more information, please visit <u>Contac</u>
Boot Color		N/A	To more mornation, piease visit <u>oonae</u>
Circuits (Loaded)		36	China ROHS Green Image
Circuits (maximum)		36	ELV Not Relevant
Durability (mating cycles max)		500	RoHS Phthalates Not Contained
Flammability		94V-0	
Gender		Plug	
Lock to Mating Part		Yes	Search Parts in this Series
Material - Metal		Phosphor Bronze	<u>52316</u> Series
Material - Plating Ma		Gold	<u>52510</u> Selles
Material - Plating Te	rmination	Tin	
Net Weight		6056.252/mg	Mates With
Number of Rows		2	<u>52822</u> , <u>54122</u> , <u>52986</u>
Orientation		N/A	
PCB Locator		No	
PCB Retention		N/A	
Packaging Type		Tray	
Panel Mount		No	
Pitch - Mating Interfa		1.27mm	
Pitch - Termination I	menace	1.27mm	
Plating min - Mating Plating min - Termin	ation	0.762µm 1.016µm	
Polarized to Mating		Yes	
Polarized to Maling Polarized to PCB	Γαιι	No	
Ports		1	
Surface Mount Com	natible (SMC)	I No	
Temperature Range		-55° to +85°C	
Termination Interfac		IDT or Pierce	
		No	
Waterproof / Dustpro Wire Insulation Dian	oof	No 0.58mm max.	

Electrical

Current - Maximum per Contact Shield Type Shielded Voltage - Maximum

**Material Info** 

**Reference - Drawing Numbers** Packaging Specification Product Specification Sales Drawing 1.0A Full Shield Yes 250V AC (RMS)/DC

SPK-52316-001-001 PS-52316-003, PS-52515-002, PS-52986-017-001 SD-52316-002

## This document was generated on 02/07/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION