

## Clip Mount Power Resistor Thick Film Technology



LTO150 are the extension of LTO series. The component is used in direct contact with heatsink. Fixation done by clip.

### ADDITIONAL RESOURCES



3D Models


### FEATURES

- 150 W at 45 °C case temperature heatsink mounted
- Direct mounting ceramic on heatsink
- Broad resistance range: 0.03 Ω to 1.3 MΩ
- Non inductive
- TO-247 package: compact and easy to mount
- Designed for clip mounting
- UL 94 V-0 material used - compliant with EN45545-2
- **AEC-Q200 qualified**
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



RoHS  
COMPLIANT

### DIMENSIONS in millimeters



#### Note

- Tolerances unless stated: ± 0.3 mm

### STANDARD ELECTRICAL SPECIFICATIONS

| MODEL   | SIZE   | RESISTANCE RANGE<br>Ω | RATED POWER<br>$P_{45\text{ °C}}$<br>W | LIMITING ELEMENT VOLTAGE $U_L$<br>V | TOLERANCE<br>± % | TEMPERATURE COEFFICIENT<br>± ppm/°C | CRITICAL RESISTANCE<br>Ω |
|---------|--------|-----------------------|--|-------------------------------------|------------------|-------------------------------------|--------------------------|
| LTO 150 | TO-247 | 0.03 to 1.3M          | 150                                    | 500                                 | 1, 2, 5, 10      | 200, 350, 900                       | 1.66K                    |

### MECHANICAL SPECIFICATIONS

|                       |               |
|-----------------------|---------------|
| Mechanical Protection | Molded        |
| Resistive Element     | Thick film    |
| Substrate             | Alumina       |
| Connections           | Tinned copper |
| Weight                | 4 g max.      |
| Clip Assembly Force   | 60 N to 110 N |

### ENVIRONMENTAL SPECIFICATIONS

|                   |  |
|-------------------|--|
| Temperature Range | -55 °C to +175 °C  |
| Climatic Category | 55 / 175 / 56  |
| Flammability      | IEC 60695-11-5<br>2 applications 30 s<br>separated by 60 s |

### TECHNICAL SPECIFICATIONS

|  |  |
|--|--|
| Dissipation and Associated                           | Onto a heatsink + clip   |
| Power Rating and Thermal Resistance of the Component | 150 W at +45 °C (case temp.)<br>$R_{TH(j-c)}$ : 0.87 °C/W<br>Free air: 4.5 W at +25 °C |
| Temperature Coefficient                              | See Performance table<br>± 200 ppm/°C  |
| Dielectric Strength IEC 60115-1                      | 3000 $V_{RMS}$ - 1 min<br>10 mA max.   |
| Insulation Resistance                                | ≥ 10 <sup>4</sup> MΩ   |
| Inductance   | ≤ 0.1 μH   |



| PERFORMANCE               |   |                               |
|---------------------------|---|-------------------------------|
| TESTS                     | CONDITIONS  | REQUIREMENTS                  |
| Momentary Overload        | IEC 60115-1<br>1.5 Pr/5 s<br>$U_S < 1.5 U_L$  | $\pm (0.5 \% + 0.005 \Omega)$ |
| Load Life                 | IEC 60115-1<br>1000 h Pr (free air) at +25 °C 90/30   | $\pm (1 \% + 0.005 \Omega)$   |
| High Temperature Exposure | AEC-Q200 REV D conditions:<br>MIL-STD-202 method 108<br>1000 h, +175 °C, unpowered                                | $\pm (0.5 \% + 0.005 \Omega)$ |
| Temperature Cycling       | AEC-Q200 REV D conditions:<br>JESD22 method JA-104<br>1000 cycles, -55 °C to +125 °C<br>dwell time -15 min        | $\pm (1 \% + 0.005 \Omega)$   |
| Biased Humidity           | AEC-Q200 REV D conditions:<br>MIL-STD-202 method 103<br>1000 h, 85 °C, 85 % RH (10 % of free air power)           | $\pm (1 \% + 0.005 \Omega)$   |
| Operational Life          | AEC-Q200 REV D conditions:<br>MIL-STD-202 method 108<br>1000 h, 90/30, powered (free air) at +125 °C              | $\pm (1 \% + 0.005 \Omega)$   |
| ESD Human Body Model      | AEC-Q200 REV D conditions:<br>AEC-Q200-002 IEC 61000-4-2<br>25 kV <sub>AD</sub>                                   | $\pm (0.5 \% + 0.005 \Omega)$ |
| Vibration                 | AEC-Q200 REV D conditions:<br>MIL-STD-202 method 204<br>5 g's for 20 min, 12 cycles<br>test from 10 Hz to 2000 Hz | $\pm (0.5 \% + 0.005 \Omega)$ |
| Mechanical Shock          | AEC-Q200 REV D conditions:<br>MIL-STD-202 method 213<br>100 g's, 6 ms, 3.75 m/s<br>3 shocks/direction             | $\pm (0.5 \% + 0.005 \Omega)$ |
| Terminal Strength         | AEC-Q200 REV D conditions:<br>AEC-Q200-006<br>2 kgf, 60 s   | $\pm (0.25 \% + 0.01 \Omega)$ |

| SPECIAL FEATURES                                       |                           |                  |                  |
|--|---------------------------|------------------|------------------|
| Resistance Values                                      | $\geq 0.03$               | $\geq 0.1$       | $> 20$           |
| Tolerances   | $\pm 1 \%$ at $\pm 10 \%$ |                  |                  |
| Typical Temperature Coefficient<br>(-55 °C to +175 °C) | $\pm 900$ ppm/°C          | $\pm 350$ ppm/°C | $\pm 200$ ppm/°C |

### CHOICE OF THE HEATSINK

The user must choose according to the working conditions of the component (power, room temperature).

Maximum working temperature must not exceed 175 °C. The dissipated power is simply calculated by the following ratio:

$$P = \frac{\Delta T}{[R_{TH(j-c)}] + [R_{TH(c-h)}] + [R_{TH(h-a)}]} \quad (1)$$

P: Expressed in W

$\Delta T$ : Difference between maximum working temperature and room temperature

$R_{TH(j-c)}$ : Thermal resistance value measured between resistive layer and outer side of the resistor. It is the thermal resistance of the component.

$R_{TH(c-h)}$ : Thermal resistance value measured between outer side of the resistor and upper side of the heatsink. This is the thermal resistance of the interface (grease, thermal pad), and the quality of the fastening device.

$R_{TH(h-a)}$ : Thermal resistance of the heatsink

#### Example:

$R_{TH(c-h)} + R_{TH(h-a)}$  for LTO 150 power rating 10 W at ambient temperature +25 °C

Thermal resistance  $R_{TH(j-c)}$ : 0.87 °C/W

Considering equation (1) we have:

$$\Delta T = 175 \text{ °C} - 25 \text{ °C} = 150 \text{ °C}$$

$$R_{TH(j-c)} + R_{TH(c-h)} + R_{TH(h-a)} = \frac{\Delta T}{P} = \frac{150}{10} = 15 \text{ °C/W}$$

$$R_{TH(c-h)} + R_{TH(h-a)} = 15 \text{ °C/W} - 0.87 \text{ °C/W} = 14.13 \text{ °C/W}$$

Example with a thermal grease  $R_{TH(c-h)} = 0.5 \text{ °C/W}$ , we need a heatsink with  $R_{TH(h-a)} = 13.63 \text{ °C/W}$

|                                  | CONFIGURATION 1 | CONFIGURATION 2 | CONFIGURATION 3 |
|----------------------------------|-----------------|-----------------|-----------------|
| Power Dissipation (W)            | 150             | 35              | 26              |
| T° Resistive Element (°C)        | 175             | 175             | 175             |
| R <sub>TH(j-c)</sub> Max. (°C/W) | 0.87            | 0.87            | 0.87            |
| R <sub>TH(c-h)</sub> Typ. (°C/W) | 0.127           | 0.33            | 0.33            |
| R <sub>TH(h-a)</sub> Max. (°C/W) | 0.069           | 3.09            | 4.57            |
| Fluid T° (°C)                    | 15 (water)      | 25 (air)        | 25 (air)        |

**CONFIGURATION 1:** Water cooling heatsink CP15 from Lytron (304 mm x 95.3 mm x 8 mm) with water flow rate 4 LPM and thermal grease Bluesil Past 340 from BlueStar silicones. MAX08NG from AAVID screwed clip mounting.

**CONFIGURATION 2:** Air cooling heatsink 0S552 from AAVID (48 mm x 80 mm x 70 mm) and thermal grease Bluesil Past 340 from BlueStar silicones. MAX03HNG from AAVID clipped mounting.


**CONFIGURATION 3:** Air cooling heatsink 0S550 from AAVID (31.75 mm x 58.7 mm x 70 mm) and thermal grease Bluesil Past 340 from BlueStar silicones. MAX03HNG from AAVID clipped mounting.

### MOMENTARY OVERLOAD


In any case the applied voltage must be lower than the maximum overload voltage of 750 V during 5 s.

### ENERGY CURVE (SINGLE PULSE)

The values indicated on the graph below are applicable to resistors in air or mounted onto a heatsink.




### POWER CURVE



### POWER RATING

The temperature of the case should be maintained within the limits specified.





### PACKAGING

Tube of 30 units

### MARKING

Model, style, resistance value (in Ω), tolerance (in %), manufacturing date, Vishay Sfernice trademark according IEC 60062.

**CLIPS**
**ACCLLTO150CL (MAX03HNG)**

**ACCLLTO150VS (MAX08NG)**

**CLIP MOUNTING RECOMMENDATION**

To improve the thermal conductivity, all surface of ceramic has to be coated with a thermal silicon grease. If you not use our clipped or screwed clip, it is recommended that a mounting force of 60 N to 110 N be applied to the center of the molding case of the component. Tightening torque 2 Nm when mounting screwed clip MAX08NG on heatsink.

| ORDERING INFORMATION |       |             |                  |                                   |   |           |                |
|----------------------|-------|-------------|------------------|-----------------------------------|---|-----------|----------------|
| LTO                  | 150   | F           | 2.7 kΩ           | ± 1 %                             | xxx   | TU30      | e3             |
| MODEL                | STYLE | CONNECTIONS | RESISTANCE VALUE | TOLERANCE                         | CUSTOM DESIGN   | PACKAGING | LEAD (Pb)-FREE |
|                      |       |             |                  | ± 1 %<br>± 2 %<br>± 5 %<br>± 10 % | Optional<br>on request:<br>special TCR,<br>shape etc. |           |                |

| GLOBAL PART NUMBER INFORMATION   |      |                  |   |   |                            |                |  |  |  |  |  |  |
|--|------|------------------|---|---|----------------------------|----------------|--|--|--|--|--|--|
| <div style="display: flex; justify-content: space-around; font-weight: bold; font-size: 1.2em;"> <span>L</span><span>T</span><span>O</span><span>1</span><span>5</span><span>0</span><span>F</span><span>2</span><span>7</span><span>0</span><span>0</span><span>0</span><span>J</span><span>T</span><span>E</span><span>3</span> </div> |      |                  |   |   |                            |                |  |  |  |  |  |  |
| GLOBAL MODEL   | SIZE | LEADS            | OHMIC VALUE   | TOLERANCE                                 | PACKAGING                  | LEAD (Pb)-FREE |  |  |  |  |  |  |
| LTO  | 150  | F = radial leads | The first four digits are significant figures and the last digit specifies the number of zeros to follow. R designates decimal point.<br>48R70 = 48.7 Ω<br>48701 = 48 700 Ω<br>10002 = 100 000 Ω<br>R0100 = 0.01 Ω<br>R4700 = 0.47 Ω<br>27000 = 2700 Ω = 2.7 kΩ | F = 1 %<br>G = 2 %<br>J = 5 %<br>K = 10 % | T = tube<br>Tube 30 pieces | E3 = pure tin  |  |  |  |  |  |  |

| CLIP PART NUMBER INFORMATION |                          |
|------------------------------|--------------------------|
| REFERENCE                    | PART NUMBER FOR ORDERING |
| Screwed clip MAX08NG         | ACCLLTO150VS             |
| Clipped clip MAX03HNG        | ACCLLTO150CL             |



## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.