

# Product data sheet

Specifications



## Rack ATS, 100/120V, 15A, 5-15 in, (10) 5-15R out



AP4450

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	100 V 120 V
Main Output Voltage	100 V 120 V
Plug standard	NEMA 5-15P
Number of rack unit	1U
Cable length	2.44 m
Number of cables	2
Provided equipment	Mounting hardware Rack mounting brackets Serial configuration cable

### Physical

Colour	Black
Height	4.4 cm
Width	43.2 cm
Depth	23.6 cm
Net weight	4.4 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted

### Input

Network frequency	50/60 Hz
[In] rated current	12 A
Input current limits	15 A
Load capacity	1440 VA

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Output

Max current draw	15 A
Number of power socket outlets	10 NEMA 5-15R

## Conformance

Product certifications	PSE TÜV-C TÜV-NURTL VCCI class A
Standards	FCC part 15 class A ICES-003

## Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

## Packing Units

Package 1 Weight	6.17 kg
Package 1 Height	11.4 cm
Package 1 width	60 cm
Package 1 Length	35.6 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------