



























# Angular Feed-Through Spring Clamp

	AS4/4			AS6/3			ADL2.5		
									
Terminal Width	6 mm			8 mm			5 mm		
Height x Length	42 x 61.5 mm			42 x 74 mm			50 x 79.5 mm		
Stripping Length	15 mm			15 mm			14 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6			Polyamide 6.6		
Type of Connection	4 spring clamp connection			3 spring clamps & 2 slots for interconnection			4 spring clamps & 4 slots for interconnection		
Approvals									
Wire Range	22-10 AWG	0.2-4 sq.mm.	22-10 AWG	22-8 AWG	0.2-6 sq.mm.	22-8 AWG	22-12 AWG	0.34-2.5 sq.mm	22-12 AWG
Voltage Rating	600 V	800 V	600 V	600 V	800 V	600 V	300 V	800 V	300 V
Current Rating	35 A	32 A	35 A	50 A	41 A	50 A	25 A	24 A	25 A
Other Approvals									
	<b>Cat. No.</b>	<b>Std. Pk.</b>		<b>Cat. No.</b>	<b>Std. Pk.</b>		<b>Cat. No.</b>	<b>Std. Pk.</b>	
<b>Terminal Block</b>	<b>AS4/4</b>	100		<b>AS6/3</b>	50		<b>ADL2.5</b>	50	
<b>End Plate</b> 	EPAS4	50		EPAS6	50		EPADL2.5	50	
<b>DIN Rail</b> for ordering information refer to pages 90-91									
<b>End Stop</b> for ordering information refer to page 92 	CA103	50		CA103	50		CA103	50	
	CA702	50		CA702	50		CA702	50	
	CA802	50		CA802	50		CA802	50	
<b>Jumpers Adjacent</b> 	DOES NOT ACCEPT JUMPERS			CA801/3	100		CA801/1	100	
<b>Jumpers Alternate</b> 				CA801/3-3	100		CA801/1-3	100	
<b>Push in type wire jumper</b> 				CA901/3	100		CA901/1	100	
<b>Step Down Jumper</b> see page 98 				CA901/4	100				
				CA901/6	100				
<b>Marking Tags</b> 	MT6	100		MT8	100		MT5	100	