## Connectedic

ER2000T-NA-CAT1



## Remarkably rugged. Extremely compact.

Operator certified, secure, and cost-effective, the ER2000T-NA-CAT1 router is designed for enterprise-grade M2M- and IoT-enabled solutions. With an innovative, lightweight design, the ER2000T-NA CAT1 is a perfect fit for even the most challenging requirements.

## Simplify network management.

The ER2000T-NA-CAT1, with its open source Linux-based OS, is ready to go right out of the box. It can be easily configured, deployed, and monitored using our cloud management portal.

## See how our routers are used worldwide.

Companies around the globe use Connected IO routers in a wide array of industries and applications, including digital signage, POS, vending machines, security, monitoring and control, and failover.

Standard:	4G LTE Category 1 with 3G fallback	ER2000T-NA-CAT1	
Speeds:	Cat 1 10Mbps download and 5Mbps upload HSPA+ 21Mbps download and 5.76Mbps upload	U.S.A., Canada AT&T, T-Mobile	
<b>D</b>		4G LTE	
Processor:	580 MHz MIPS 24K CPU Core; 128MB of DDR2 RAM	Band 2 (1900 MHz)	
Connectivity:	Two 10/100BASE-T Ethernet ports (RJ-45 connector)	Band 4 (1700 MHz)	
	One RS-232 (DE-9) port with configurable GPIO One mini-USB 2.0 OTG connector; 0.5A power	Band 5 (850 MHz)	
	One 2FF UICC card slot	Band 12 (700 MHz)	
	Four SMA connectors (two for LTE and two for Wi-Fi)	Band 13 (700 MHz)	
Antennas:	Four SMA dipole antennas (included)	3G	
Wi-Fi:	2x2 MIMO 2.4-GHz 802.11b/g/n	Band 2 (1900 MHz)	
Network, Routing	: IPV4, IPV6, static routing, port forwarding and DHCP server, MAC filtering	Band 5 (850 MHz)	
VPN:	OpenVPN IPSEC Tunnel via StrongSwan	IN THE BOX	
Embedded OS:	OpenWRT (Linux based)		
OS compatibility:	Linux 2.6.16 or later; Android KitKat (4.4) or later; Windows 10, 8.1, 8, 7, CE; Windows Mobile 6.5		
Power input:	12V DC 2A		
Operating temp:	-20°C to 55°C		
Compliance:	LTE Category 1 3GPP Release 9		
Certifications:	FCC Part 15 Class B, CE, CISPR Class B, PTCRB, RCM, RoHS, AT&T, T-Mobile, Industry Canada		
Dimensions:	HeightWidthDepthWeight3.92 inches4.51 inches1.01 inch5.5 oz		

(99.6 mm)	(114.6 mm)	(24.7 mm)	
Copyright © 2017 Connected IO Inc. All rights reserved. PB-ER2000T-NA-CAT1-20171201			

connectedio.com Downloaded from Arrow.com. (156 g)