



Search within category

GO

BUY NOW

DESIGN / INSTALL



FSD78-8-K

Insulated ferrules, single wire black DIN end sleeve on mini-reel, 16 AWG (1.5mm²), 0.31" (8.0mm) pin length.

[Specs](#)
[Tools](#)
[Documents](#)

[★ Add to Favorites](#)
[🛒 Add to BOM](#)

| | |
|-----------------------------------|---|
| Std. Pkg. Qty. | 1000 |
| Product Type | Ferrules on Reel |
| Pin Length In. (mm) | 0.31 (8) |
| Style | Single Wire |
| Wire Range In. (mm ²) | 16 AWG (1.5) |
| Barrel Type | Seamless |
| Base Material | Copper |
| Insulation | Polypropylene |
| Panduit Color Code | Black |
| Plating Type | Tinned |
| Part Number Series | FSD |
| Length In (mm) | 0.57 (14.5) |
| Max. Insulation Diameter In. (mm) | 0.13 (3.2) |
| Wire Strip Length In. (mm) | 13/32" (.4062) - (10mm) |
| Flammability Rating | HB |
| Temperature Rating | 221 Degrees Fahrenheit (105 Degrees Celsius) |
| Tool | CP-881, CA10, Uni-A-FA (SCA-712022002) |
| CSA Certified | C22.2 No. 291-14 |
| Standards | DIN 46228 Part 1, UL 486F Listed, UL 508A Certified |
| Packaging Type | Mini Reel |
| Pieces Per Reel | 1000 |
| CE Compliant | No |
| Inside Diameter (In.) | 0.07 |
| Inside Diameter (mm) | 1.8 |
| Length (In.) | 0.57 |
| Length (mm) | 14.5 |
| Outside Diameter (In.) | 0.08 |
| Outside Diameter (mm) | 2.1 |
| Part Features | <ul style="list-style-type: none"> • Polypropylene insulation housing available in DIN standard colors in reels to 3000 or 5000 • Designed specifically for use with the Ferrule Applicator (CA10) for high volume applications • Continuously molded design provides consistent placement of ferrules in applicator to ensure fast, reliable terminations |
| Wire Range | 16 AWG |
| RoHS Compliancy Status | Compliant |
| Min. Order Qty. | 1,000.0000 |