

SD Card / Micro SD Card


MMRD4



MURD4



GENERAL INFORMATION

| | | | | |
|---------------------------------|--|---|---|---|
| TYPE | SD MEMORY CARD (SD / SDHC) | | microSD MEMORY CARD (SD / SDHC) | |
| INTERFACE DATA TRANSFER MODE | SD 3.0, UHS-I/Class 10 (SDHC) , Class 6 (SD) | | | |
| CONNECTOR | SD | | microSD | |
| OUTLINE DIMENSIONS | 32 x 24 x 2.1 mm | | 15 x 11 x 0.7 / 1 mm | |
| SERIES | MMRD4 | | MURD4 | |
| CONTROLLER TYPE |  TDK GBDriver RD4 | | | |
| FLASH TYPE | SLC | pSLC | SLC | pSLC |
| DENSITY RANGE | 512 MB - 32 GB | 4 GB - 32 GB | 512 MB - 2 GB | 4 GB - 32 GB |
| DATA RETENTION | 10 years @ life begin-10% 1 year @ life end | | | |
| ENDURANCE ENTERPRISE WL | 512 MB ~ 2 GB:50,000 P/E Cycles 4 GB ~ 32 GB:100,000 P/E Cycles *Flash Block Level | 20,000 P/E Cycles *Flash Block Level | 50,000 P/E Cycles *Flash Block Level | 20,000 P/E Cycles *Flash Block Level |

TEMPERATURE

| | |
|-----------------------|--|
| OPERATING TEMPERATURE | Commercial: -25°C to +85°C Industrial: -40°C to +85°C |
| STORAGE TEMPERATURE | -40°C to +85°C |

PERFORMANCE

| | | | | |
|--------------|--------------|--------------|--------------|--------------|
| Read (max.) | 75 MByte/sec | 70 MByte/sec | 75 MByte/sec | 70 MByte/sec |
| Write (max.) | 50 MByte/sec | 67 MByte/sec | 50 MByte/sec | 67 MByte/sec |

ROBUSTNESS

| | | |
|-----------|--------------------------------|-------------------|
| MTBF | ≥ 3,000,000 hours | ≥ 3,000,000 hours |
| SHOCK | 1000G,0.5ms | |
| VIBRATION | 15G,10-2000Hz | |
| HUMIDITY | 0 to 90 % RH (No condensation) | |

ELECTRICAL DATA

| | |
|-------------------|--|
| VOLTAGE | 2.7 ~ 3.6 V |
| POWER CONSUMPTION | <ul style="list-style-type: none"> - Read: 100mA max. - Write: 100mA max. - Stand-by: 0.4mA |

FEATURE LIST

| | | |
|------------------|--|----------------------|
| FEATURES & TOOLS | <ul style="list-style-type: none"> - In-House Designed Controller - Power Fail Data Safety - Global static wear leveling - SMART | |
| PART NUMBER | MMRD4xxxxVxxxA00AAA0 | MURD4xxxxVxxxA00AAA0 |