

NetCommander USB Server Interface Unit (SIU) - 8-Pack

MODEL NUMBER: B078-101-USB-8



Features

- 8-Pack of B078-101-USB-1 Server Interface Units
- Needed to connect a USB Server to a B070 / B072-Series NetCommander KVM switch via Cat5e cable
- Eliminates the need for thicker, heavier KVM cables
- Compact, lightweight design
- · Plug and Play; no software required
- No power supply required
- Allows a Server/CPU to be located up to 100-ft. (30.5 m) away from the KVM switch
- To convert DisplayPort or HDMI computers to VGA, use Tripp Lite adapters P134-06N-VGA-V2 or P131-06N
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Highlights

- 8-Pack of B078-101-USB-1 Server Interface Units
- Needed to connect a USB Server to a B070 / B072-Series NetCommander KVM switch via Cat5e cable
- Easy to install; no software needed
- No power supply required
- Allows a recommended maximum distance of 100-ft. (30.5 m) from KVM to computer/server via Cat5e cable
- · Compact and lightweight design

System Requirements

- Server or CPU with a HD15 port and a USB port
- A B070 / B072-Series NetCommander Cat5 KVM Switch
- Cat5e/6 cable; up to 100ft
- To convert DisplayPort or HDMI computers to VGA, use Tripp Lite adapters P134-06N-VGA-V2 or P131-06N

Package Includes

• (x8) B078-101-USB-1 USB Server Interface Units (SIU)

Specifications

| OVERVIEW | | |
|----------------------|------------------------|--|
| UPC Code | 037332182470 | |
| Accessory Type | Server Interface Unit | |
| Technology | Cat5/5e; VGA/SVGA | |
| Accessory Class | KVM Switch Accessories | |
| INPUT | | |
| Bus Powered | Yes | |
| Product Length (ft.) | 1.3 | |



| USER INTERFACE, ALERTS & CONTROLS | | |
|--|---|--|
| LED Indicators | GREEN (RECEIVING POWER); ORANGE (SELECTED AS ACTIVE PORT) | |
| PHYSICAL | | |
| Color | Gray | |
| Material of Construction | ABS | |
| Shipping Dimensions (hwd / in.) | 4.50 x 6.00 x 10.30 | |
| Shipping Dimensions (hwd / cm) | 11.43 x 15.24 x 26.16 | |
| Shipping Weight (lbs.) | 2.20 | |
| Shipping Weight (kg) | 1.00 | |
| Unit Packaging Type | Box | |
| Unit Weight (lbs.) | 0.18 | |
| Unit Weight (kg) | 0.08 | |
| CONNECTIONS | | |
| Side A - Connector 1 | HD15 (MALE) | |
| Side A - Connector 2 | USB A (MALE) | |
| Side B - Connector 1 | RJ45 (FEMALE) | |
| Computer Keyboard and Mouse Interface | USB | |
| Computer Monitor Interface | VGA | |
| FEATURES & SPECIFICATIONS | | |
| Driver Required | No | |
| Recommended Category Cable | N105 - SERIES CAT5E SHIELDED CABLES | |
| IP68 Rated | No | |
| IP20 Rated | No | |
| STANDARDS & COMPLIANCE | | |
| Product Certifications | EN 55022; EN 55024 | |
| Product Compliance | RoHS; CE (Europe); REACH; FCC (USA) | |
| WARRANTY & SUPPORT | | |
| Product Warranty Period (Worldwide) | 3-year limited warranty | |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

https://www.tripplite.com/products/product-certification-agencies