

# Home Inspection Kit Model REED-INSPECT-KIT





### **Features**

## Model 8706 Digital Psychrometer

- Simultaneous display of %RH, temperature and dew point or wet bulb
- Optional external probe (87P6) for contact/differential temperature measurement
- Max/Min/Avg readings
- Fast response
- Data Hold Function
- User selectable °F/°C
- · Low battery indicator and auto shut-off

## Model R6015 Wood Moisture Detector

- Measures wood moisture with integrated pins or with remote hand-press probe
- Improved accuracy with use of included automatic temperature compensation probe
- Memory contains 8 wood groups with calibrations for approx. 170 species of wood
- Built-in 2-point calibration check
- · Low battery indicator and auto shut-off

| Model            | Description         |
|------------------|---------------------|
| REED-INSPECT-KIT | Home Inspection Kit |

# TECHNICAL DATA

#### Model R6010 Pinless Moisture Meter

- Non-invasive measurements, run sensor over surface being tested without scratching or penetrating the surface
- Classifies moisture status as: dry, at risk or wet
- Detects moisture content in various building materials
- Measurement depth from 0.8" (20 mm) to 1.6" (40 mm)
- Data Hold and Min/Max functions
- User adjustable alarms with audible and visual indicators
- Large backlit LCD display
- Low battery indicator and auto shut-off

## Model R8005 Laser Distance Meter

- Designed for one-handed operation
- User selectable unit of measure (imperial/metric)
- Laser target pointer
- Reference point selection (front or rear of instrument)
- Backlit multi-line LCD display
- Quick, self calculation with real-time readout
- Area. Volume and Max/Min functions
- Addition, Subtraction and indirect 2/3 point (Pythagoras) calculations
- Integrated bubble level (horizontal and vertical)
- Continuous measurement mode
- Internal memory saves up to 99 readings
- Low battery indicator and auto shut off

## Model R2300 Infrared Thermometer

- Built-in laser pointer identifies target area
- User selectable °F or °C
- 12:1 distance to spot size ratio
- Digitally adjustable emissivity
- Max and Min readings
- Backlit display
- High and low alarms
- · Low battery indication and auto shut off

## Model R9950 Soft Carrying Case

- · Accommodates up to 3 small to medium sized instruments
- Built-in elastics and compartments help organize instruments
- Adjustable shoulder strap and hand strap
- Made of polyester
- Internal dimensions: 12 x 9.5 x 2" (305 x 241 x 51 mm)
- External dimensions: 12.5 x 10 x 2.5" (318 x 254 x 64 mm)
- Weight: 8.2 oz (232 g)