



## TS-431KX-2G

CPU	AnnapurnaLabs, an Amazon company Alpine AL214, 4-core, 1.7GHz
CPU Architecture	32-bit ARM
Floating Point Unit	Yes
Encryption Engine	Yes
System Memory	2 GB SODIMM DDR3 (1 x 2 GB)
Maximum Memory	8 GB (1 x 8 GB)
Memory Slot	1 x SODIMM DDR3
Flash Memory	512 MB (Dual boot OS protection)
Drive Bay	4x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Hot-swappable	Yes
SSD Cache Acceleration Support	Yes
Gigabit Ethernet Port (RJ45)	2
10 Gigabit Ethernet Port	1 x 10GbE SFP+
Wake on LAN (WOL)	Yes
Jumbo Frame	Yes
USB 3.2 Gen 1 port	3
Form Factor	Tower
LED Indicators	Power, Status, LAN, USB, HDD1-4
Buttons	Power, Reset, USB Auto Copy

Dimensions (HxWxD)	6.65 × 6.3 × 8.62 inch
Weight (Net)	4.43 lbs
Weight (Gross)	7.65 lbs
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	90W adapter (12VDC), 100-240VAC
Power Consumption: HDD Sleep Mode	11.65 W
Power Consumption: Operating Mode, Typical	26.7 W
Fan	1 x 120mm, 12VDC
System Warning	Buzzer
Kensington Security Slot	Yes
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	400

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.