


- Ultra low ripple and noise 10mVp-p typ.
- Compact SIP-8 package
- Input Voltage range 4.5-13.2, 9-18, 18-36, 36-75 VDC
- I/O isolation 1600 VDC
- Operating temperature range -40 to +75°C without derating
- Fully regulated outputs
- Short circuit protection
- 3-year product warranty



The TVN 3 Series comprises ultra low ripple and noise 3 Watt DC/DC converters. They come in a compact SIP-8 package with fully regulated outputs. Apart from the standard 2:1 input voltage range, the low input voltage models feature an extended input voltage range from 4.5-13.2 VDC (3:1). Full load operation is reliable up to 75°C environment temperature without derating and up to 90°C with 50% derating. With 1'600 VDC I/O-isolation voltage, and short current protection they cover a wide range of applications when space is limited.

Models						
Order Code	Input Voltage Range	Output 1		Output 2		Efficiency typ.
		Vnom	I <sub>max</sub>	Vnom	I <sub>max</sub>	
TVN 3-0910	4.5 - 13.2 VDC (9 VDC nom.)	3.3 VDC	700 mA			75 %
TVN 3-0911		5 VDC	600 mA			79 %
TVN 3-0919		9 VDC	333 mA			81 %
TVN 3-0912		12 VDC	250 mA			83 %
TVN 3-0913		15 VDC	200 mA			83 %
TVN 3-0915		24 VDC	125 mA			82 %
TVN 3-0921		+5 VDC	300 mA	-5 VDC	300 mA	78 %
TVN 3-0922		+12 VDC	125 mA	-12 VDC	125 mA	82 %
TVN 3-0923		+15 VDC	100 mA	-15 VDC	100 mA	82 %
TVN 3-1210		9 - 18 VDC (12 VDC nom.)	3.3 VDC	700 mA		
TVN 3-1211	5 VDC		600 mA			81 %
TVN 3-1219	9 VDC		333 mA			83 %
TVN 3-1212	12 VDC		250 mA			85 %
TVN 3-1213	15 VDC		200 mA			85 %
TVN 3-1215	24 VDC		125 mA			84 %
TVN 3-1221	+5 VDC		300 mA	-5 VDC	300 mA	80 %
TVN 3-1222	+12 VDC		125 mA	-12 VDC	125 mA	84 %
TVN 3-1223	+15 VDC		100 mA	-15 VDC	100 mA	83 %
TVN 3-2410	18 - 36 VDC (24 VDC nom.)		3.3 VDC	700 mA		
TVN 3-2411		5 VDC	600 mA			82 %
TVN 3-2419		9 VDC	333 mA			85 %
TVN 3-2412		12 VDC	250 mA			85 %
TVN 3-2413		15 VDC	200 mA			85 %
TVN 3-2415		24 VDC	125 mA			85 %
TVN 3-2421		+5 VDC	300 mA	-5 VDC	300 mA	80 %
TVN 3-2422		+12 VDC	125 mA	-12 VDC	125 mA	85 %
TVN 3-2423		+15 VDC	100 mA	-15 VDC	100 mA	85 %
TVN 3-4810		36 - 75 VDC (48 VDC nom.)	3.3 VDC	700 mA		
TVN 3-4811	5 VDC		600 mA			80 %
TVN 3-4819	9 VDC		333 mA			83 %
TVN 3-4812	12 VDC		250 mA			84 %
TVN 3-4813	15 VDC		200 mA			85 %
TVN 3-4815	24 VDC		125 mA			84 %
TVN 3-4821	+5 VDC		300 mA	-5 VDC	300 mA	80 %
TVN 3-4822	+12 VDC		125 mA	-12 VDC	125 mA	85 %
TVN 3-4823	+15 VDC		100 mA	-15 VDC	100 mA	83 %

### Input Specifications

Input Current	- At no load	9 Vin models: <b>55 mA typ.</b> 12 Vin models: <b>30 mA typ.</b> 24 Vin models: <b>16 mA typ.</b> 48 Vin models: <b>12 mA typ.</b>
Surge Voltage		9 Vin models: <b>15 VDC max.</b> (1 s max.) 12 Vin models: <b>25 VDC max.</b> (1 s max.) 24 Vin models: <b>50 VDC max.</b> (1 s max.) 48 Vin models: <b>100 VDC max.</b> (1 s max.)
Under Voltage Lockout		9 Vin models: <b>2 VDC min. / 3 VDC typ. / 4 VDC max.</b> 12 Vin models: <b>6 VDC min. / 7 VDC typ. / 8 VDC max.</b> 24 Vin models: <b>13 VDC min. / 15 VDC typ. / 17 VDC max.</b> 48 Vin models: <b>29 VDC min. / 32 VDC typ. / 35 VDC max.</b>
Recommended Input Fuse		(The need of an external fuse has to be assessed in the final application.)
Input Filter		<b>Internal Capacitor</b>

### Output Specifications

Voltage Set Accuracy		<b>±1% max.</b>
Regulation	- Input Variation (Vmin - Vmax)	single output models: <b>0.2% max.</b> dual output models: <b>0.2% max.</b>
	- Load Variation (0 - 100%)	single output models: <b>1% max.</b> dual output models: <b>1% max. (Output 1)</b> <b>1% max. (Output 2)</b>
	- Cross Regulation (25% / 100% asym. load)	dual output models: <b>5% max.</b>
Ripple and Noise	- 20 MHz Bandwidth	<b>10 mVp-p typ.</b> <b>15 mVp-p max.</b>
Capacitive Load	- single output	3.3 Vout models: <b>4'400 µF max.</b> 5 Vout models: <b>2'200 µF max.</b> 9 Vout models: <b>1'300 µF max.</b> 12 Vout models: <b>1'000 µF max.</b> 15 Vout models: <b>820 µF max.</b> 24 Vout models: <b>470 µF max.</b>
	- dual output	5 / -5 Vout models: <b>1'200 / 1'200 µF max.</b> 12 / -12 Vout models: <b>520 / 520 µF max.</b> 15 / -15 Vout models: <b>440 / 440 µF max.</b>
Minimum Load		<b>Not required</b>
Temperature Coefficient		<b>±0.02 %/K max.</b>
Start-up Time		<b>30 ms typ.</b>
Short Circuit Protection		<b>Continuous, Automatic recovery</b>
Transient Response	- Response Time	<b>500 µs typ. (25% Load Step)</b>

### Safety Specifications

Safety Standards	- IT / Multimedia Equipment	<b>Designed for EN 62368-1 (no certification)</b>
------------------	-----------------------------	---

### EMC Specifications

EMI Emissions	- Conducted Emissions	<b>EN 55032 class A (with external filter)</b> <b>EN 55032 class B (with external filter)</b>
	- Radiated Emissions	<b>EN 55032 class A (with external filter)</b> <b>EN 55032 class B (with external filter)</b>
		External filter proposal: <a href="http://www.tracopower.com/overview/tvn3">www.tracopower.com/overview/tvn3</a>

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

EMS Immunity	- Electrostatic Discharge	Air: EN 61000-4-2, ±8 kV, perf. criteria A
	- RF Electromagnetic Field	Contact: EN 61000-4-2, ±6 kV, perf. criteria A
	- EFT (Burst) / Surge	EN 61000-4-3, 10 V/m, perf. criteria A
		EN 61000-4-4, ±2 kV, perf. criteria A
		EN 61000-4-5, ±1 kV, perf. criteria A
	- Conducted RF Disturbances	Ext. input component: 220 µF, 100 V
	- PF Magnetic Field	Continuous: EN 61000-4-6, 10 Vrms, perf. criteria A
		1 s: EN 61000-4-8, 100 A/m, perf. criteria A
		1 s: EN 61000-4-8, 1000 A/m, perf. criteria A

## General Specifications


Relative Humidity		95% max. (non condensing)
Temperature Ranges	- Operating Temperature	-40°C to +90°C
	- Storage Temperature	-55°C to +125°C
Power Derating	- High Temperature	3.33 %/K above 75°C
Cooling System		Natural convection (20 LFM)
Remote Control	- Current Controlled Remote	On: open circuit
		Off: 2 to 4 mA current (internal 1 kΩ resistor)
	- Off Idle Input Current	2.5 mA max.
Switching Frequency		100 kHz min. (PFM)
Insulation System		Functional Insulation
Isolation Test Voltage	- Input to Output, 60 s	1'600 VDC
	- Input to Case, 60 s	1'000 VDC
	- Output to Case, 60 s	1'000 VDC
Isolation Resistance	- Input to Output, 500 VDC	1'000 MΩ min.
Isolation Capacitance	- Input to Output, 100 kHz, 1 V	1'500 pF max.
Reliability	- Calculated MTBF	5'600'000 h (MIL-HDBK-217F, ground benign)
Washing Process		Allowed (hermetical product)
	See Cleaning Guideline:	<a href="http://www.tracopower.com/info/cleaning.pdf">www.tracopower.com/info/cleaning.pdf</a>
Environment	- Vibration	MIL-STD-810F
	- Thermal Shock	MIL-STD-810F
Housing Material		Copper
Potting Material		Silicone (UL 94 V-0 rated)
Pin Material		Copper
Pin Foundation Plating		Nickel (1 - 2 µm)
Pin Surface Plating		Tin (3 - 5 µm), matte
Housing Type		Metal Case
Mounting Type		PCB Mount
Connection Type		THD (Through-Hole Device)
Footprint Type		SIP8
Weight		5.9 g
Environmental Compliance	- REACH Declaration	<a href="http://www.tracopower.com/info/reach-declaration.pdf">www.tracopower.com/info/reach-declaration.pdf</a>
		REACH SVHC list compliant
		REACH Annex XVII compliant
	- RoHS Declaration	<a href="http://www.tracopower.com/info/rohs-declaration.pdf">www.tracopower.com/info/rohs-declaration.pdf</a>
		Exemptions: 7a, 7c-I
		(RoHS exemptions refer to the component concentration only, not to the overall concentration in the product (O5A rule). The SCIP number is provided on request.)

## Supporting Documents

Overview Link (for additional Documents)	<a href="http://www.tracopower.com/overview/tvn3">www.tracopower.com/overview/tvn3</a>
--	--

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

### Outline Dimensions



Dimensions in [mm], ( ) = Inch  
 Tolerances: x.x ±0.5 (±0.02)  
 Tolerances: x.xx ±0.25 (±0.01)  
 Pin pitch tolerances ±0.25 (±0.01)  
 Pin dimension tolerance ±0.1 (±0.004)

Pinout		
Pin	Single	Dual
1	-Vin (GND)	-Vin (GND)
2	+Vin (VCC)	+Vin (VCC)
3	Remote On/Off	Remote On/Off
5	NC	NC
6	+Vout	+Vout
7	-Vout	Common
8	NC	-Vout
9	Case	Case
10	Stand off	Stand off
11	Stand off	Stand off
12	Case	Case

NC: No connection