



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4 X.XX=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. RATING: 0.4VA @ 20V AC or DC max.
 5. FIXED TERM. MOVING CONTACT: COPPER ALLOY with GOLD Plate over Nickel plate
 6. ELECTRICAL LIFE: 50,000 make-and-break cycle at full load.
 7. DIELECTRIC STRENGTH: 1,000 V RMS @sea level.
 8. OPERATING TEMP.: -30°C to 85°C
 9. ▲ DENOTES CRITICAL PARAMETER.
 10. 2002/95/EC (ROHS) COMPLIANT

D	16058	EDIT DIMENSIONS	5/30/06	CT					
C	12575	CHANGE CAP PART NUMBER	12/14/04	AR					
B	14222	REF. DIM WAS 6.51	8/11/04	AR					
A	13571	RELEASED FOR PRODUCTION	11/3/03	AR					
REV.	ECN No.	DESCRIPTION	DATE	CHKD					
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED					SCALE	DATE	DR	DWG	REV
					2:1	11/3/03	AR	XT0121P	D
					E-SWITCH® 800AWS P8M7REC2BLK				