

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of CSTCW24M0X53-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=CSTCW24M0X53-R0

CSTCW24M0X53-R0










Appearance & Shape







Features

MURATA's package technology expertise has enabled the development of the Chip CERALOCK(R) with built-in load capacitors. High-density mounting can be realized because of the small package and the elimination of the need for an external load

Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. Available in a wide frequency range.
- 3. Extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.



Applications

Other Usage	Consumer/Industrial
-------------	---------------------



Packaging Information

Packaging	Specifications	Standard Packing Quantity
R0	180mm Embossed Tape	3000

1 of 2

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

Please download the latest datasheet of CSTCW24M0X53-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=CSTCW24M0X53-R0

Note: This datasheet may be out of date.

CSTCW24M0X53-R0



Specifications

Product Type	Ceramic Resonator	
Troduct Typo	(CERALOCK)	
Series	CSTCW_X	
Frequency	24.000MHz	
Frequency Tolerance	+/-0.50% max.	
Operating Temperature Range	-20°C~80°C	
Frequency Shift by	40.0004	
Temperature	+/-0.20% max.	
Frequency Aging	+/-0.10% max.	
Resonant Impedance (R1)	80ohm max.	
Built-in Load Capacitance (CL1/CL2)	15pF	
Shape	SMD	
Wash	Not available	
L x W (size)	2.5x2.0mm	
Mass	32mg	

2 of 2

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

