

**PRODUCT NUMBER: 1618-0-57-15-00-00-03-0**

**1618-X-XX-15-00-00-03-0**  
 Low profile Target Discs, surface mount

Contact Style	Target Disc Height (A)	Tape Pocket Depth (B)	Tape Pocket Opening (C)	Quantity per Reel
0	.025	.035	.151	7,200
1	.035	.045	.151	6,000
2	.045	.055	.151	5,125
3	.055	.065	.151	4,000
4	.065	.075	.152	3,850

**DESCRIPTION**

Spring-Loaded Target Contact with Flat Face

**Current Rating:**

Application Specific

**Operating Temperature Range:**

-55/+125° C (discontinuous)

**Mounting Feature:**

Surface Mount

**Packaging:** 57 - Vertically on Tape & Reel

<b>Shell Plating</b>	<b>Contact Plating</b>	<b>ROHS</b>
----------------------	------------------------	-------------

10 μ" Gold over Nickel



**ADDITIONAL NOTES & SPECIFICATIONS**

In the interest of improved design, quality and performance, Mill-Max reserves the right to make changes in its specifications without prior notice. Specifications and tolerances are provided wherever possible. Due to the wide variety of interconnects Mill-Max offers, the specific tolerances vary from product to product. If you need information regarding the tolerance of a particular part, please contact Technical Services.

© 2020 Mill-Max Mfg. Corp.  
 190 Pine Hollow Rd , Oyster Bay, NY 11771, USA  
 Phone: 516.922.6000

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mill-Max:

[1618-0-57-15-00-00-03-0](#)