


# 2729-125

125 Watts, 36 Volts, 100 $\mu$ s, 10%  
Radar 2700-2900 MHz

<p><b>GENERAL DESCRIPTION</b></p> <p>The 2729-125 is an internally matched, COMMON BASE bipolar transistor capable of providing 125 Watts of pulsed RF output power at 100<math>\mu</math>s pulse width, 10% duty factor across the 2700 to 2900 MHz band. <b>The transistor prematch and test fixture has been optimized through the use of Pulsed Automated Load Pull.</b> This hermetically solder-sealed transistor is specifically designed for S-band radar applications. It utilizes gold metallization and emitter ballasting to provide high reliability and supreme ruggedness.</p>	<p><b>CASE OUTLINE</b> <b>55KS-1</b> <b>Common Base</b></p> 
<p><b>ABSOLUTE MAXIMUM RATINGS</b></p> <p><b>Maximum Power Dissipation</b> Device Dissipation @ 25°C<sup>1</sup>                      350 W</p> <p><b>Maximum Voltage and Current</b> Collector to Base Voltage (BV<sub>ces</sub>)                      65 V Emitter to Base Voltage (BV<sub>ebo</sub>)                      3.0 V Collector Current (I<sub>c</sub>)                                      15 A</p> <p><b>Maximum Temperatures</b> Storage Temperature                                      -65 to +200 °C Operating Junction Temperature                      +200 °C</p>	

## ELECTRICAL CHARACTERISTICS @ 25°C

SYMBOL	CHARACTERISTICS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
P <sub>out</sub>	Power Output	F=2700-2900 MHz	125			W
P <sub>in</sub>	Power Input	V <sub>cc</sub> = 36 Volts			15.7	W
P <sub>g</sub>	Power Gain	Pulse Width = 100 $\mu$ s	9.0	9.5		dB
$\eta_c$	Collector Efficiency	Duty Factor = 10%	45	55		%
VSWR	Load Mismatch Tolerance <sup>1</sup>	F = 2900 MHz, P <sub>o</sub> = 125W			2:1	

## FUNCTIONAL CHARACTERISTICS @ 25°C





BV <sub>ebo</sub>	Emitter to Base Breakdown	I <sub>e</sub> = 30 mA	3.0			V
BV <sub>ces</sub>	Collector to Emitter Breakdown	I <sub>c</sub> = 120 mA	56	65		V
h <sub>FE</sub>	DC – Current Gain	V <sub>ce</sub> = 5V, I <sub>c</sub> = 600 mA	18	50		
$\theta_{jc}$ <sup>1</sup>	Thermal Resistance				0.5	°C/W


NOTE: 1. At rated output power and pulse conditions


Issue April 2003

Vcc = 36 Volts, Pulse Width = 100µs, Duty = 10%

G2747-2, Unit 7, TF040803P2







# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Microchip:](#)

[2729-125](#)