Product Brief

Intel® Wi-Fi 6 AX200 Module
1st Generation Wi-Fi 6 (802.11ax1) Solution



Intel® Wi-Fi 6 AX200 (Gig+) Module

Nearly 3X higher peak data rates and up to 4X capacity





The Intel® Wi-Fi 6 AX200 (Gig+) adapter supports the new IEEE 802.11ax standard – Wi-Fi 6 technology and is Wi-Fi CERTIFIED 6™1. The product supports 2x2 Wi-Fi 6 technology, including new features such as UL and DL OFDMA and 1024QAM, delivering data rates of up to 2.4Gbps² and increased network capacity as well as Bluetooth® 5.2 support. These new features deliver a significant improvement in user experience in dense deployments, supporting fast uploads and downloads, lower latency, and longer battery life compared to solutions supporting 802.11ac. Combined with Intel® Core™ processors and exceptional Intel wireless innovations, the Intel® Wi-Fi 6 AX200 module can provide Gigabit wireless speed² and dramatically improve your connected experience at home, work, or on the go.

1st Generation Intel Wi-Fi 6 Wireless

Increased Capacity Faster Speed Better Coverage	By implementing the new 802.11ax standard with its unique features such as OFDMA, 1024QAM, Target Wake Time (TWT), and spatial reuse, Intel® Wi-Fi 6 AX200 module enables smooth streaming of high-resolution videos, fewer dropped connections, and faster connections farther away from the router and in dense environments.	
Extended Battery Life 802.11ax Dual Band 2x2 160MHz Improved Security	When using Wi-Fi 6 technology with 1024QAM and 160MHz channels, Intel® Wi-Fi 6 AX200 module can deliver nearly 3x higher peak data rates³ (up to 2.4Gbps) and up to 4x capacity improvement in dense or congested environments comparing to 802.11ac⁴. Intel® Wi-Fi 6 AX200 module supports the new WPA3* security features, enabling next-generation authentication and military-grade encryption.	
Bluetooth® 5.2	Bluetooth® 5.2 provides 4x ⁵ range over Bluetooth® 4.2 using the same Tx power, enabling coverage throughout the home. Bluetooth® 5.2 also doubles data rates speed for faster transmissions thereby reducing the overall power consumption ⁵ . Additionally, Bluetooth® 5.2 adds new enhanced data broadcasting, enabling seamless location-based services and simpler pairing for Bluetooth® devices.	
Microsoft Windows 10*	Full support for the latest Microsoft Windows 10* OS.	
Form Factors (M.2 2230 and 1216)	M.2 2230 modules enable system configuration and platform usage flexibility with the use of a standard Key A or Key E socket for attaching the module.	

M.2 1216 modules enable platform design providing savings on motherboard space and BOM.

Experience the Intel® Differ	ence		
Worldwide Regulatory Support Intel® Dynamic Regulatory Solution	Enables performance optimized worldwide regulatory compliance SKU. The Intel® Wi-Fi 6 AX200 module detects its location and automatically optimizes the Wi-Fi settings to local regulatory requirements, maximizing performance in each geography, simplifying travel experience and global enterprise procurement. Future regulatory changes are easily managed during the productific cycle.		
Wireless Functionality in Pre- boot Environment	Support for Wi-Fi network and Bluetooth® Low Energy Human Interface Device (HID) connectivity the platform's UEFI (Unified Extensible Firmware Interface) environment during its boot stage. The capability enables use cases like OS recovery over Wi-Fi and Bluetooth® Low Energy-based keyboard and mouse connectivity in this pre-boot environment.		
Wirelessly Project to the Big Screen	Project your 2-in-1 or laptop content instantly, without wires, on the big HD screen with stunning image clarity and sound using Wi-Fi Miracast*. Stream movies, videos, games, photos, connect wifriends, and more. Experience it all, bigger and better than ever before.		
Business-Class Wireless			
Intel® vPro® Technology ⁶	Supports Intel's hardware-based security and management features built into Intel® Core™ vPro® processors and chipsets that enable IT to manage PCs virtually anywhere, anytime, while reducing deployment costs, improving security and ROI.		
Intel® Active Management Technology ⁷	Using integrated platform capabilities and popular third-party management and security applications, Intel® AMT allows IT or managed service providers to better discover, repair, and he protect their networked computing assets. Intel® AMT is a feature of Intel® Core™ processors with Intel® vPro® technology.		
Intel® WI-FI 6 AX200 Modul	e Technical Specifications		
Intel® WI-FI 6 AX200 Modul GENERAL	e Technical Specifications		
GENERAL	e Technical Specifications M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)] M.2 1216: 12mm x 16mm x 1.67 (+-0.08) mm		
GENERAL Dimensions (H x W x D)	M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)]		
GENERAL Dimensions (H x W x D) Weight	M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)] M.2 1216: 12mm x 16mm x 1.67 (+-0.08) mm M.2 2230: 2.83 +/- 0.3 g		
GENERAL Dimensions (H x W x D) Weight Radio ON/OFF Control	M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)] M.2 1216: 12mm x 16mm x 1.67 (+-0.08) mm M.2 2230: 2.83 +/- 0.3 g M.2 1216: 0.67 +/- 0.1 g		
GENERAL Dimensions (H x W x D) Weight Radio ON/OFF Control Connector Interface Operating Temperature	M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)] M.2 1216: 12mm x 16mm x 1.67 (+-0.08) mm M.2 2230: 2.83 +/- 0.3 g M.2 1216: 0.67 +/- 0.1 g Supported		
GENERAL Dimensions (H x W x D) Weight Radio ON/OFF Control Connector Interface Operating Temperature (Adapter Shield)	M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)] M.2 1216: 12mm x 16mm x 1.67 (+-0.08) mm M.2 2230: 2.83 +/- 0.3 g M.2 1216: 0.67 +/- 0.1 g Supported M.2: PCle*, USB		
GENERAL Dimensions (H x W x D) Weight Radio ON/OFF Control Connector Interface Operating Temperature (Adapter Shield) Humidity Non-Operating	M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)] M.2 1216: 12mm x 16mm x 1.67 (+-0.08) mm M.2 2230: 2.83 +/- 0.3 g M.2 1216: 0.67 +/- 0.1 g Supported M.2: PCle*, USB 0°C to +80°C		
GENERAL Dimensions (H x W x D) Weight Radio ON/OFF Control Connector Interface Operating Temperature (Adapter Shield) Humidity Non-Operating Operating Systems	M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)] M.2 1216: 12mm x 16mm x 1.67 (+-0.08) mm M.2 2230: 2.83 +/- 0.3 g M.2 1216: 0.67 +/- 0.1 g Supported M.2: PCle*, USB 0°C to +80°C 50% to 90% RH non-condensing (at temperatures of 25°C to 35°C)		
GENERAL Dimensions (H x W x D) Weight Radio ON/OFF Control Connector Interface Operating Temperature (Adapter Shield) Humidity Non-Operating Operating Systems Wi-Fi Alliance ⁸	M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)] M.2 1216: 12mm x 16mm x 1.67 (+-0.08) mm M.2 2230: 2.83 +/- 0.3 g M.2 1216: 0.67 +/- 0.1 g Supported M.2: PCle*, USB 0°C to +80°C 50% to 90% RH non-condensing (at temperatures of 25°C to 35°C) Microsoft Windows* 10, Linux*, Chrome OS* Wi-Fi CERTIFIED* 6, Wi-Fi CERTIFIED* a/b/g/n/ac, WMM*, WMM*-Power Save, WPA2*, WPA3*, WPS*, PMF*,		
GENERAL Dimensions (H x W x D) Weight Radio ON/OFF Control Connector Interface Operating Temperature (Adapter Shield) Humidity Non-Operating Operating Systems Wi-Fi Alliance ⁸ IEEE WLAN Standard	M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)] M.2 1216: 12mm x 16mm x 1.67 (+-0.08) mm M.2 2230: 2.83 +/- 0.3 g M.2 1216: 0.67 +/- 0.1 g Supported M.2: PCle*, USB 0°C to +80°C 50% to 90% RH non-condensing (at temperatures of 25°C to 35°C) Microsoft Windows* 10, Linux*, Chrome OS* Wi-Fi CERTIFIED* 6, Wi-Fi CERTIFIED* a/b/g/n/ac, WMM*, WMM*-Power Save, WPA2*, WPA3*, WPS*, PMF*, Wi-Fi Direct*, Wi-Fi Agile Multiband* and Wi-Fi TimeSync* IEEE 802.11-2016 and select amendments (selected feature coverage)		
GENERAL Dimensions (H x W x D) Weight Radio ON/OFF Control Connector Interface Operating Temperature (Adapter Shield) Humidity Non-Operating Operating Systems Wi-Fi Alliance ⁸ EEEE WLAN Standard	M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)] M.2 1216: 12mm x 16mm x 1.67 (+-0.08) mm M.2 2230: 2.83 +/- 0.3 g M.2 1216: 0.67 +/- 0.1 g Supported M.2: PCle*, USB 0°C to +80°C 50% to 90% RH non-condensing (at temperatures of 25°C to 35°C) Microsoft Windows* 10, Linux*, Chrome OS* Wi-Fi CERTIFIED* 6, Wi-Fi CERTIFIED* a/b/g/n/ac, WMM*, WMM*-Power Save, WPA2*, WPA3*, WPS*, PMF*, Wi-Fi Direct*, Wi-Fi Agile Multiband* and Wi-Fi TimeSync* IEEE 802.11-2016 and select amendments (selected feature coverage) IEEE 802.11a, b, d, e, g, h, i, k, n, r, u, v, w, ac, ax; Fine Timing Measurement based on 802.11-2016		
GENERAL Dimensions (H x W x D) Weight Radio ON/OFF Control Connector Interface Operating Temperature (Adapter Shield) Humidity Non-Operating Operating Systems Wi-Fi Alliance ⁸ HEEE WLAN Standard Bluetooth [®] SECURITY FEATURES ⁹	M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)] M.2 1216: 12mm x 16mm x 1.67 (+-0.08) mm M.2 2230: 2.83 +/- 0.3 g M.2 1216: 0.67 +/- 0.1 g Supported M.2: PCle*, USB 0°C to +80°C 50% to 90% RH non-condensing (at temperatures of 25°C to 35°C) Microsoft Windows* 10, Linux*, Chrome OS* Wi-Fi CERTIFIED* 6, Wi-Fi CERTIFIED* a/b/g/n/ac, WMM*, WMM*-Power Save, WPA2*, WPA3*, WPS*, PMF*, Wi-Fi Direct*, Wi-Fi Agile Multiband* and Wi-Fi TimeSync* IEEE 802.11-2016 and select amendments (selected feature coverage) IEEE 802.11a, b, d, e, g, h, i, k, n, r, u, v, w, ac, ax; Fine Timing Measurement based on 802.11-2016		
	M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)] M.2 1216: 12mm x 16mm x 1.67 (+-0.08) mm M.2 2230: 2.83 +/- 0.3 g M.2 1216: 0.67 +/- 0.1 g Supported M.2: PCle*, USB 0°C to +80°C 50% to 90% RH non-condensing (at temperatures of 25°C to 35°C) Microsoft Windows* 10, Linux*, Chrome OS* Wi-Fi CERTIFIED* 6, Wi-Fi CERTIFIED* a/b/g/n/ac, WMM*, WMM*-Power Save, WPA2*, WPA3*, WPS*, PMF*, Wi-Fi Direct*, Wi-Fi Agile Multiband* and Wi-Fi TimeSync* IEEE 802.11-2016 and select amendments (selected feature coverage) IEEE 802.11a, b, d, e, g, h, i, k, n, r, u, v, w, ac, ax; Fine Timing Measurement based on 802.11-2016 Bluetooth* 5.2		

COMPLIANCE	
Regulatory	For a list of country approvals, please contact your local Intel representatives.
US Government	FIPS ¹⁰ 140-2
Product Safety	UL, C-UL, CB (IEC 60950-1)

Product Name	Model Number	Version
Intel® Wi-Fi 6 AX200	AX200NGW AX200D2WL	Wi-Fi 6 (802.11ax), 2x2, Bluetooth® 5.2, M.2 2230 Wi-Fi 6 (802.11ax), 2x2, Bluetooth® 5.2, M.2 1216; LTE Coex

For more information on Intel® Wireless products, visit intel.com/wireless





- ¹ Wi-Fi 6 (802.11ax) WFA certification is available since September 2019.
- ² Based on the theoretical maximum bandwidth enabled by 2x2 802.11ax 160MHz implementations. Actual wireless throughput and/or range will vary depending on your specific operating system, hardware and software configurations. Check with your device manufacturer for details.
- ³ "Nearly 3X higher peak data rates" Intel® Wi-Fi 6 AX claims are based on the comparison of the expected maximum theoretical data rates for similarly configured 802.11ax and standard 802.11ac Wi-Fi solutions as documented in IEEE 802.11ax draft 2.0 spec and IEEE 802.11 wireless standard specifications, and require the use of similarly configured 802.11ax wireless network routers.
- ⁴ In accordance with the IEEE 802.1ax PAR. For additional details, visit: https://mentor.ieee.org/802.11/dcn/14/11-14-0165-01-0hew-802-11-hew-sg-proposed-par.docs
- 5 Bluetooth® 5.2 Feature overview, https://www.bluetooth.com/wp-content/uploads/2020/01/Bluetooth_5.2_Feature_Overview.pdf. Only mandatory features are supported.
- ⁶ Intel* vPro* Technology is sophisticated and requires setup and activation. Availability of features and results will depend upon the setup and configuration of your hardware, software and IT environment. To learn more visit: http://www.intel.com/technology/vpro.
- Requires activation and a system with a corporate network connection, an Intel® AMT-enabled chipset, network hardware and software. For notebooks, Intel® AMT may be unavailable or limited over a host OS-based VPN, when connecting wirelessly, on battery power, sleeping, hibernating or powered off. Results dependent upon hardware, setup and configuration. For more information, visit http://www.intel.com.
- ⁸ Support of Wi-Fi Alliance certifications is OS-dependent.
- 9 Some security solutions may not be supported by your device operating system and/or by your device manufacturer or may require additional hardware (e.g., UICC SIM card). Check with your device manufacturer for details on availability.
- ¹⁰ On Microsoft Windows 10*.

The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Intel Corporation is under license.

Tests document performance of components on a particular test, in specific systems. Differences in hardware, software, or configuration will affect actual performance. Consult other sources of information to evaluate performance as you consider your purchase. For more complete information about performance and benchmark results, visit www.intel.com/benchmarks.

Estimated results were obtained prior to implementation of recent software patches and firmware updates intended to address exploits referred to as "Spectre" and "Meltdown". Implementation of these updates may make these results inapplicable to your device or system.

No license (express or implied, by estoppel or otherwise) to any intellectual property rights is granted by this document.

Intel disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. Intel may make changes to specifications and product descriptions at any time, without notice. For the most current product information, please visit http://www.intel.com/wireless.

Cost reduction scenarios described are intended as examples of how a given Intel-based product, in the specified circumstances and configurations, may affect future costs and provide cost savings. Circumstances will vary. Intel does not guarantee any costs or cost reduction.

This device has not been authorized as required by the rules of the Federal Communications Commission. This device is not, and may not be, offered for sale or lease, or sold or leased, until authorization is obtained.

Intel, the Intel logo, are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

* Other names and brands may be claimed as the property of others.

Copyright © Intel Corporation. All rights reserved.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Intel:

AX200.D2WG.L AX200.D2WG.LNV AX200.D2WG.LTNV AX200.D2WG.LTNV AX200.D2WG.LNVP AX200.D2WG.LTNP AX200.D2WG.LP