

Qwik RJ45™ Cat6/Cat5E Modular Plugs

Stewart Connector's Qwik RJ45™ CAT6/CAT5E Modular Plugs are designed to be terminated to industry standard CAT5E and CAT6 cables while reducing assembly time and improving termination quality in the field.

Qwik RJ45™ CAT6/CAT5E Modular Plugs allow the installer to insert the cable into the connector prior to trimming conductors to required length. Stewart Connector's 2940263-02 termination tool trims the cable conductors to required length while terminating the plug contacts. The Qwik RJ45™ Modular Plug eliminates the pre-trim step needed to assemble traditional RJ45 Modular Plugs reducing termination time.

Features & Benefits

- Designed for quick and easy field termination
- CAT5E and CAT6 performance rated
- 50 micro inches of gold plating on contacts
- Contact designed for use on solid or stranded conductor cable
- Terminates to cable diameter of up to .235"
- Accommodates conductor diameters of .037" to .042"
- Designed to terminate 24AWG and 26AWG conductors
- Optional snagless slimline strain relief boot available
- Capable of field or factory termination with Stewart Connector 2940263-02 or other available quick termination tools

Part Number	Description
SS-39500-001	Qwik RJ45™ CAT6/CAT5E Plug Pack of 50
SS-39500-002	Qwik RJ45™ CAT6/CAT5E Plug Pack of 100
SS-39500-003	Strain Relief Boot CAT6/CAT5E, Pack of 50
SS-39500-004	Strain Relief Boot CAT6/CAT5E, Pack of 100
SS-39500-005	Qwik RJ45™ CAT6/CAT5E Plug With boot, Pack of 50
SS-39500-006	Qwik RJ45™ CAT6/CAT5E Plug With boot, Pack of 100
2940263-02	Qwik RJ45™ Termination Tool
2905090-02	Qwik RJ45™ Replacement Trim Blades for Termination Tool



Stewart Connector
11118 Susquehanna Trail South
Glen Rock, PA 17327-9199

+1 717.235.7512
techhelp@belf.com
belfuse.com/stewart-connector

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Bel:](#)

[SS-39500-004](#) [SS-39500-002](#) [SS-39500-005](#) [SS-39500-003](#) [SS-39500-001](#) [2905090-02](#) [SS-39500-006](#) [2940263-02](#)