



### Model Number: SB-PET-ES

Working temperature: -50°C ~ +150°C

Melting point: 250°C±5

Flame resistant grade: UL VW-1

### Structure

Expandable sleeving is braided with environment-friendly polyester monofil. (PET, PA, PPS), It possesses good flexibility, fire resistance, abrasive resistance and thermal insulation performance. The sleeving owns smooth surface, bright color, various patterns.

### Usage & Main Parameters

Expandable sleeving is widely used in bounding and protecting of electrical cables, automobile and aviation sectors.

The selection of this product refers to following four parameters.

1. yarn number (one or three or more);
2. Diameter of single yarn (0.20mm or 0.25mm)

### Dimension

Model Number	Flat Width Size (mm)	Min Width (mm)	Max Width (mm)	Packing (Meters/ Roll)
SB-PET-ES-003	3	1	6	500
SB-PET-ES-006	6	3	9	500
SB-PET-ES-008	8	5	16	500
SB-PET-ES-010	10	7	19	500
SB-PET-ES-012	12	8	24	500
SB-PET-ES-016	16	10	27	250
SB-PET-ES-019	19	14	30	250
SB-PET-ES-025	25	18	35	200
SB-PET-ES-030	30	20	50	200
SB-PET-ES-038	38	30	60	100
SB-PET-ES-045	45	35	75	100
SB-PET-ES-050	50	40	80	100
SB-PET-ES-060	60	45	105	50
SB-PET-ES-070	70	60	110	50
SB-PET-ES-080	80	64	120	50

\*Other sizes could be customized.

**Color:** The standard color is black, other colors upon customer's requirement.