

Fire-resistant& Heat-resistant fiberglass sleeving



Model Number: SB-SGS-FH

Continuous working temperature :-60°C to +260°C

Peak at

-30mim at 800°C

-15mim at 1100°C

-1 min at 1500°C

-30s at 1650°C

Structure

It is braided by non-alkali fiberglass sleeving and coated with silicone rubber.

Characteristics

Fireproof, flame retardant, high temperature resistant, heat resistant, insulation, anti-aging, anti-molten steel splash, waterproof, anti-oil, anti-acid,etc.

Application

Cable assemblies, water, gas, compressed air and hydraulic fluid ducts, steel industry, foundries, steelworks, glassworks, chemical and petrochemical industry, ship-building, railways,aeronautic and space industry, etc.

Dimension

Inner Diameter		Thickness (mm)	Standard Package (m/roll)
MM	Inch		
6.0	1/4	1.5	20
8.0	5/16	1.6	20
10.0	3/8	1.8	20
13.0	1/2	1.9	20
15.0	5/8	2.1	20
20.0	3/4	2.4	20
25.0	1	2.6	20
30.0	11/8	2.9	20
32.0	11/4	3.0	20
35.0	13/8	3.1	20
40.0	15/8	3.4	20
45.0	13/4	3.4	20
50.0	2	3.6	20
55.0	21/4	3.7	20
60.0	23/8	3.8	20
65.0	21/2	3.8	20
70.0	23/4	4.0	20
75.0	3	4.1	20
80.0	31/8	4.3	20
90.0	31/2	4.5	20
100.0	4	4.6	20

*Other size can be produced upon request.

Color: Standard color is rust red, other color available upon request.