



Model Number: SBD-DWGW & SBD-SWHFW

Working temperature: -45°C ~ 125°C

Structure

Heavy wall heat shrinkable tube is manufactured by co-extrusion polyolefin and environment friendly hot-melt adhesive. It is designed to provide both insulation and sealing for protected articles. Both adhesive-lined and without adhesive are available.

Characteristics

It has heavy wall, semi-rigid, sealing, insulation, damp proof performances. It is mainly used in electronics, electricity, telecommunications, automobile, shipping, aerospace manufacturing etc.

Usage

1. Shrink ratio: 3:1
2. Shrink temperature: 70°C ~ 125°C
3. Heavy wall, semi-rigid, insulated, excellent sealing performance

Dimension

1) Flame Retardant Heavy Wall Heat Shrinkable Tube with Adhesive Lined

Inner Diameter (mm)	ID As Supplied (mm)	After Recovery(mm)				Standard Package (m/pcs)
		ID	Outer Layer Thickness	Adhesive Thickness	Whole Wall Thickness	
9/3	≥9	≤3	2.0±0.20	0.35±0.10	2.30±0.25	1.22
13/4	≥13	≤4	2.4±0.20	0.35±0.10	2.75±0.25	1.22
20/6	≥20	≤6	2.5±0.20	0.40±0.10	2.90±0.25	1.22
28/9	≥28	≤9	2.5±0.20	0.40±0.10	2.90±0.25	1.22
33/10.2	≥33	≤10.2	3.2±0.20	0.40±0.10	3.60±0.25	1.22
38.1/12	≥38.1	≤12	3.4±0.20	0.60±0.15	4.00±0.30	1.22
43.2/12	≥43.2	≤12	4.3±0.20	0.70±0.20	5.00±0.35	1.22
55/16	≥55	≤16	4.3±0.20	0.70±0.20	5.00±0.35	1.22
75/22	≥75	≤22	4.3±0.20	0.70±0.20	5.00±0.35	1.22
85/25	≥85	≤25	4.3±0.20	0.70±0.20	5.00±0.35	1.22
105/30	≥105	≤30	4.3±0.20	0.80±0.25	5.10±0.35	1.22
120/36	≥120	≤36	4.3±0.20	0.80±0.25	5.10±0.35	1.22
130/36	≥130	≤36	4.3±0.20	0.80±0.25	5.10±0.35	1.22
140/42	≥140	≤42	4.3±0.20	0.80±0.25	5.10±0.35	1.22

2) Flame Retardant Heavy Wall Heat Shrinkable Tube without Adhesive Lined

Inner Diameter (mm)	ID As supplied (mm)	After Recovery(mm)		Standard Package (m/pcs)
		ID	Whole Wall Thickness	
9/3	≥9	≤3	2.30±0.25	1.22
13/4	≥13	≤4	2.75±0.25	1.22
20/6	≥20	≤6	2.90±0.25	1.22
28/9	≥28	≤9	2.90±0.25	1.22
33/10.2	≥33	≤10.2	3.60±0.25	1.22
38.1/12	≥38.1	≤12	4.00±0.30	1.22
43.2/12	≥43.2	≤12	5.00±0.35	1.22
55/16	≥55	≤16	5.00±0.35	1.22
75/22	≥75	≤21	5.00±0.35	1.22
85/25	≥85	≤25	5.00±0.35	1.22
105/30	≥105	≤30	5.10±0.35	1.22
120/36	≥120	≤36	5.10±0.35	1.22
130/36	≥130	≤36	5.10±0.35	1.22
140/42	≥140	≤42	5.10±0.35	1.22

Color: Standard color is black (other color available upon request).