

## Military Grade Heat Shrink Marker Sleeve



**Model number: SBD-SWHF-MG**

Working temperature: -55°C ~ +135 °C

### Structure

Military grade heat shrink marker sleeve is developed environment-friendly flame retardant heat shrinkable tube, using specially designed formulation of high polymers, through cross-link by electronic accelerator and continuous expansion.

### Usage

SB-SWHF-MG markers are widely used in military industry, aerospace and marine.

### Characteristics

Material	The sleeving shall be fabricated from irradiated, thermally stabilized and flame retarded modified polyolefin compound
Application range	Military industry; Aerospace & defense; Marine;
Operating temperature range	-55°C ~ +135°C
Minimum recovery temperature	+85°C
Maximum storage temperature	+50°C
Shrink ratio	2:1, 3:1
Color	White, Yellow, other color is available if ordered
Printing mode	Single sided printing and Double sided printing formats available
Supplied mode	Either Continuous type or Ladder format type is available
Recommended Printers	Either Thermal transfer printer or Laser printer is OK.

### Specification: Shrink ratio-2X

Model Number	As Supplied (mm)			After Recovery(mm)	
	ID(D)	Flatten Width(W2)	Double Wall Thickness	ID(d)	Single Wall Thickness
SWHF-MG-2X-1.6-50-2.5K	2.00±0.20	3.7±0.3	0.48±0.10	≤0.79	0.45±0.06
SWHF-MG-2X-2.4-50-2.5K	2.79±0.20	5.0±0.3	0.48±0.10	≤1.18	0.49±0.06
SWHF-MG-2X-3.2-50-2.0K	3.64±0.23	6.3±0.4	0.48±0.10	≤1.59	0.51±0.06
SWHF-MG-2X-4.8-50-2.0K	5.26±0.25	8.9±0.4	0.49±0.10	≤2.36	0.54±0.06
SWHF-MG-2X-6.4-50-1.5K	6.92±0.28	11.5±0.4	0.50±0.10	≤3.18	0.56±0.06
SWHF-MG-2X-9.5-50-1.0K	10.2±0.32	16.7±0.5	0.51±0.11	≤4.75	0.59±0.06
SWHF-MG-2X-12.7-50-1.0K	13.5±0.36	21.8±0.6	0.52±0.11	≤6.35	0.60±0.07
SWHF-MG-2X-19-50-0.5K	20.1±0.40	32.2±0.6	0.53±0.11	≤9.53	0.62±0.07
SWHF-MG-2X-25-50-0.5K	26.7±0.45	42.5±0.7	0.55±0.12	≤12.7	0.63±0.07
SWHF-MG-2X-38-50-0.5K	39.8±0.51	63.2±0.8	0.57±0.12	≤19.1	0.64±0.07

**SHEN ZHEN SUNBOW INSULATION MATERIALS MFG.CO.,LTD.**

SWHF-MG-2X-51-50-0.25K	53.0±0.56	83.9±0.9	0.58±0.13	≤25.4	0.64±0.08
SWHF-MG-2X-76-50-0.25K	79.4±0.56	125.3±1.0	0.59±0.13	≤38.1	0.64±0.09

**Specification: Shrink ratio-3X**

Model Number	As Supplied (mm)			After Recovery(mm)	
	ID(D)	Flatten Width(W2)	Double Wall Thickness	ID(d)	Single Wall Thickness
SWHF-MG-3X-1.6-50-2.5K	2.00±0.20	3.7±0.3	0.47±0.10	≤0.53	0.52±0.06
SWHF-MG-3X-2.4-50-2.5K	2.79±0.20	5.0±0.3	0.47±0.10	≤0.79	0.57±0.06
SWHF-MG-3X-3.2-50-2.0K	3.64±0.23	6.3±0.4	0.48±0.10	≤1.06	0.61±0.06
SWHF-MG-3X-4.8-50-2.0K	5.26±0.25	8.9±0.4	0.49±0.10	≤1.59	0.67±0.06
SWHF-MG-3X-6.4-50-1.5K	6.92±0.28	11.5±0.4	0.50±0.10	≤2.36	0.71±0.06
SWHF-MG-3X-9.5-50-1.0K	10.2±0.32	16.7±0.5	0.52±0.11	≤3.18	0.77±0.06
SWHF-MG-3X-12.7-50-1.0K	13.5±0.36	21.8±0.6	0.53±0.11	≤4.75	0.80±0.07
SWHF-MG-3X-19-50-0.5K	20.1±0.40	32.2±0.6	0.55±0.11	≤6.35	0.84±0.07
SWHF-MG-3X-25-50-0.5K	26.7±0.45	42.5±0.7	0.56±0.12	≤8.47	0.86±0.07
SWHF-MG-3X-38-50-0.5K	39.8±0.51	63.2±0.8	0.57±0.12	≤12.9	0.89±0.07
SWHF-MG-3X-51-50-0.25K	53.0±0.56	83.9±0.9	0.57±0.13	≤17.2	0.90±0.08
SWHF-MG-3X-76-50-0.25K	79.4±0.56	125.3±1.0	0.57±0.13	≤25.8	0.92±0.09

**Color:** Standard color is white and yellow. Other colors are available if ordered.

SWHF - MG- 3X - 1.6 - 50 - 2.5K

