



Model Number: SB-SRS-70

Rated ambient temperature: 200°C, rated voltage: 600V

Structure

It is extruded by silicone rubber, and reinforced with non-alkaline fiberglass braid, then coated with silicone resin and treated.

Characteristics

Superior flame resistant, bendability, electrical properties and mechanical strength.

Usage

H&N grade automobile, shipbuilding, electrical machinery, home electrical appliances, electric & heat equipment, special lightware, etc.

Dimension

Inner Diameter / mm		Wall Thick mm	Standard package m/roll
Nominal /mm	Tolerance /mm		
1.0mm	+0.20, -0.10	1.00±0.15mm	100
1.5mm	+0.30, -0.20	1.00±0.15mm	100
2.0mm	+0.30, -0.20	1.00±0.15mm	100
2.5mm	+0.30, -0.20	1.00±0.15mm	100
3.0mm	+0.30, -0.20	1.00±0.15mm	100
3.5mm	+0.30, -0.20	1.00±0.15mm	100
4.0mm	+0.40, -0.20	1.05±0.15mm	100
4.5mm	+0.40, -0.20	1.10±0.20mm	100
5.0mm	+0.40, -0.20	1.10±0.20mm	100
6.0mm	+0.40, -0.20	1.10±0.20mm	100
7.0mm	+0.50, -0.30	1.10±0.20mm	50
8.0mm	+0.50, -0.30	1.10±0.20mm	50
9.0mm	+0.50, -0.30	1.10±0.20mm	50
10.0mm	+1.00, -0.50	1.10±0.20mm	50
12.0mm	+1.00, -0.50	1.30±0.25mm	50
14.0mm	+1.00, -0.50	1.50±0.25mm	50
16.0mm	+1.00, -0.50	1.50±0.25mm	50
18.0mm	+1.00, -0.50	1.80±0.25mm	25
20.0mm	+1.50, -1.00	2.10±0.25mm	25

*Other size can be customized.

Package: Packing by rolls or cut upon request.

Color: Standard color is white, other color available upon request.