

Non-shrinkable halogen free flame resistance polyolefin tubing



**Model Number: SBD-SWHF-PO**

Working temperature: -55°C ~ 125°C

**Structure**

Non-shrinkable halogen free flame resistance polyolefin tubing is made of eco-friendly cross-linking polyolefin material under irradiation. It has excellent physical and chemical electrical performance. The main function is to connect pieces of electrical insulation and wiring harness.

**Usage**

It is mainly used in electronics, telecommunication, automobiles,

shipping and other manufacturing industries.

**Characteristics**

1. Non-shrinkable, Irradiated
2. Halogen free, flame-retardant, flexible, non-toxic, low smoke,
3. RoHS compliant
4. Standard color: Black

**Table 1: Specification**

Property	Unit	Standard	Test Method
Tensile Strength	MPA	≥10.4(before aging)	ASTM D 2671
		≥7.3(after aging)	158°C*168h
Breakage Elongation (%)	%	≥200(before aging)	ASTM D 149
		≥100(after aging)	158°C*168h
Heat Shock	-	no sticking & no cracking	UL 224, 250°C*4h
Volume Resistivity	Ω. cm	≥1×10 <sup>14</sup>	IEC 60093
Corrosion Performance	-	PASS	UL224
Flammability	-	VW-1, Self-extinguishing	UL224
Water absorption	%	≤0.5	ASTM D570
Dielectric Strength	KV/mm	≥15	IEC 243

**Table2: Dimension**

Size (AWG)	Inner diamter (mm)	Thin wall thickness (mm)	Normal wall thickness (mm)	Standard package (m/spool)
AWG20	0.85±0.05	0.20±0.02	0.30±0.02	200
AWG18	1.00±0.05	0.30±0.02	0.40±0.02	200
AWG16	1.30±0.05	0.30±0.02	0.40±0.02	200
AWG14	1.65±0.05	0.30±0.02	0.40±0.02	200
AWG12	2.10±0.05	0.30±0.02	0.40±0.02	100
AWG10	2.60±0.05	0.35±0.02	0.50±0.02	100
AWG8	3.30±0.05	0.35±0.02	0.50±0.02	100
AWG6	4.10±0.05	0.35±0.02	0.50±0.02	50
AWG5	4.60±0.05	0.35±0.02	0.50±0.02	50
AWG4	5.20±0.05	0.35±0.02	0.50±0.02	50
AWG3	5.80±0.05	0.35±0.02	0.50±0.02	50
AWG2	6.50±0.05	0.40±0.02	0.50±0.02	50
AWG1	7.40±0.05	0.40±0.02	0.50±0.02	50
AWG0	8.30±0.05	0.40±0.02	0.50±0.02	50
3/8	9.50±0.10	0.50±0.02		50
7/16	11.1±0.10	0.50±0.02		50
1/2	12.7±0.10	0.50±0.02		50
9/16	14.3±0.10	0.60±0.03		50
5/8	15.9±0.10	0.60±0.03		50
11/16	17.5±0.10	0.60±0.03		50
3/4	19.1±0.10	0.70±0.03		50
7/8	22.2±0.10	0.70±0.03		25
15/16	23.8±0.10	0.70±0.03		25
1	25.4±0.10	0.70±0.03		25

**Color:** Standard color is black, white, red, yellow, green, blue (other color available upon request).