

PFA Tube



Model Number: SBD-PFA

Working temperature: -200°C ~ +255°C

Usage

For semiconductor manufacturing equipment, heat exchangers, steam piping, high-purity reagent delivery pipes, various corrosive medium (harsh solvent) delivery pipes, various frequency wire and cable sheaths, groove insulation pipes, all-inclusive fluoroplastic O-rings Tube.

Specification

Corrosion resistance, water absorption, non-flammability, pentotoxicity, high light transmittance, weather resistance, easy secondary processing.

Dimension for Ordinary Tube

External Diameter x Internal Diameter(mm)	Maximum Length(m)	External Diameter x Internal Diameter(mm)	Maximum Length(m)
Φ 2 X Φ 1.6	100-500	Φ 16 X Φ 13	50-100
Φ 3 X Φ 2.2		Φ 16 X Φ 14	
Φ 4 X Φ 3.2		Φ 20 X Φ 16	
Φ 5 X Φ 4		Φ 20 X Φ 18	
Φ 6 X Φ 3		Φ 25 X Φ 21	
Φ 6 X Φ 4		Φ 25 X Φ 22	
Φ 6 X Φ 5		Φ 32 X Φ 28	
Φ 8 X Φ 6		Φ 32 X Φ 29	
Φ 8 X Φ 7		Φ 36 X Φ 30	
Φ 10 X Φ 7		Φ 36 X Φ 32	
Φ 10 X Φ 8		Φ 40 X Φ 34	
Φ 10 X Φ 9		Φ 40 X Φ 36	
Φ 12 X Φ 10		Φ 42 X Φ 38	
Φ 12 X Φ 11		Φ 46 X Φ 42	
Φ 16 X Φ 12		Φ 50 X Φ 46	

Dimension for precision tube

External Diameter x Internal Diameter(mm)	External Diameter x Internal Diameter(mm)	Length(m)
Φ 1.87 X Φ 1.28	Φ 4.50 X Φ 3.74	200-500
Φ 1.94 X Φ 1.28	Φ 4.70 X Φ 3.74	
Φ 2.16 X Φ 1.50	Φ 5.00 X Φ 4.12	
Φ 2.56 X Φ 1.90	Φ 5.00 X Φ 4.24	
Φ 2.62 X Φ 1.98	Φ 5.24 X Φ 4.24	
Φ 2.62 X Φ 2.06	Φ 5.34 X Φ 4.58	
Φ 3.00 X Φ 2.44	Φ 5.70 X Φ 4.94	
Φ 3.53 X Φ 2.83	Φ 6.00 X Φ 5.24	
Φ 3.53 X Φ 2.93	Φ 6.26 X Φ 5.24	
Φ 4.50 X Φ 3.64	Φ 6.99 X Φ 5.99	

Standard color is clear, Other color and size can be customized as requested.