

## PET Braided Self Closing Cable Wrap



### Model Number: SB-SC-B

Working temperature: -50°C ~ +150°C

Material: PET+PPS

Melting point: 240°C±10

Flame resistant grade: UL1441 VW-1

### Structure

PET braided Self-closing cable wrap offers innovative solutions to the protection of breakout areas and also provides ease of removal when inspection or maintenance of cables is required. The special open structure allows it can be installed after necessary components, for examples copper terminals and connectors. Strong resilience force keeps the wire or the cables not exposed,

meanwhile provides excellent abrasion resistance and flame-resistance.

### Usage

It is widely used in the protection of various lines such as electronic appliances, high-speed rail industry, automobile industry, communication industry, automation equipment, etc., especially suitable for those that need protection and heat dissipation.

### Dimension

Model Number	Inner diameter(mm)	Max application diameter	Packing(meters/Roll)
SB-SC-B-005	5	6	100
SB-SC-B-008	8	9	100
SB-SC-B-010	10	11	100
SB-SC-B-013	13	14	100
SB-SC-B-016	16	17	50
SB-SC-B-019	19	20	50
SB-SC-B-025	25	27	25
SB-SC-B-030	30	32	25
SB-SC-B-038	38	40	25
SB-SC-B-050	50	52	25

**Color:** The standard color is black, other colors upon customer's requirement.