

## Slit Type Corrugated Pipe



### Model Number: SB- OTCP (slit type)

Working temperature: -30°C ~ +100°C (PE material)

-40°C ~ +110°C (PP material)

-40°C ~ +125°C (PA material)

### Performance

Good flexibility, abrasion resistance, acid resistance, fire resistance, etc.

Structure: wavy shape both interior and exterior.

### Usage

It can be used in machinery, electrical equipment, foodstuff machinery, automatic meters and gauges and motors as abrasion and insulation protection for cables.

### Dimension

Material	Item No.	Size (mm)		Packing (meters/roll)
		Inner Diameter	Outer Diameter	
PE, PP, PA Slit Type Corrugated Pipe	AD7.0	5.0	7.0	500
	AD7.5	5.5	7.5	500
	AD9.0	6.0	9.0	500
	AD10.0	7.0	10.0	500
	AD11.0	8.0	11.0	500
	AD12.0	9.0	12.0	500
	AD13.0	10.0	13.0	500
	AD14.0	11	14	200
	AD15.8	12.0	15.8	200
	AD18.5	14.3	18.5	200
	AD19.0	15	19	200
	AD21.2	17.0	21.2	200
	AD22.0	18.0	22.0	100
	AD23.0	19.0	23.0	100
	AD25.0	20.0	25.0	100
	AD27.0	22.0	27.0	100
	AD28.5	23.0	28.5	100
	AD30.0	25.0	30.0	100
	AD32.0	27.0	32.0	100
AD34.5	29.0	34.5	100	
AD42.5	36.0	42.5	50	
AD54.5	48.0	54.5	25	

\*Other sizes could be customized.

**Color:** Standard color is black (other color available upon request).