

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

UPS Replacement Battery Cartridge for select APC UPS, 5.5-lbs.

MODEL NUMBER: RBC2A



Description

Tripp Lite's premium UPS replacement battery cartridges breathe new life into UPS systems suffering from expired or weak internal batteries. Each replacement battery set is carefully configured to meet or exceed all of the original manufacturer specifications and ships pre-assembled and ready for installation into your UPS system. Reusable packaging holds expired batteries for recycling center delivery. Compatible with select UPS systems from APC and other major brands. See Tripp Lite's UPS replacement battery page to confirm compatibility and quantity required.

Features

- Restores your UPS to its original runtime specifications
- Comes pre-assembled and ready for installation into your UPS system
- Reusable packaging holds expired batteries for recycling center delivery
- Compatible with many brands and models, including APC models BK200, BK250B, BK280B, BP280, BP280PNP, BP280C, BP280S, BK300, BK350, BK400, BK400B, BP420, BP420C, BP420PNP, BP420S, BK500M, PCPER, PCPRO, SUVS420, SU420NET, BP350UC, BP500CLR, BP500UC

Specifications

OVERVIEW		
UPC Code	037332118394	
BATTERY		
Typical Battery Lifespan	3 - 5 years, depending on host UPS operating conditions	
PHYSICAL		

Highlights

- Up to 30% longer runtime than basic replacements
- OEM certified premium batteries
- Rugged, leakproof construction
- Maintenance-free
- Wide operating temperature range

Package Includes

- UPS battery replacement cartridge
- Instruction manual with installation, recycling and warranty information



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Shipping Dimensions (hwd / cm)	15.49 x 19.05 x 30.23	
Shipping Dimensions (hwd / in.)	6.10 x 7.50 x 11.90	
Shipping Weight (kg)	3.81	
Shipping Weight (lbs.)	8.40	
Unit Dimensions (hwd / cm)	9.4 x 6.4 x 14.9	
Unit Dimensions (hwd / in.)	3.6875 x 2.5 x 5.875	
Unit Weight (kg)	2.49	
Unit Weight (lbs.)	5.5	
ENVIRONMENTAL		
Relative Humidity	0 - 95% non-condensing	
Operating Elevation (ft.)	0 - 10,000	
Storage Elevation (ft.)	0 - 50,000	
Operating Elevation (m)	0-3000 m	
Storage Elevation (m)	0 - 15,200 m	
WARRANTY		
Product Warranty Period (U.S. & Canada)	18-month limited warranty	
Product Warranty Period (International)	1-year limited warranty	
Product Warranty Period (Mexico)	1-year limited warranty	
Product Warranty Period (Puerto Rico)	1-year limited warranty	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies