

BP24V28-2U

External Battery Pack for UPS Systems



Model #: BP24V28-2U

- ▶ Extends runtime of select compatible Tripp Lite UPS Systems with 24VDC external battery connector
- ▶ Simple installation; 2U rackmount, tower and stack adaptable
- ▶ 2-year warranty

DESCRIPTION

BP24V28-2U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 2 rack spaces (2U). Includes heavy gauge cabling with high current DC connector for simple installation.

Compatible UPS Systems - SU1000RTXL2Ua, SMART750RMXL2U, and other Tripp Lite UPS systems that specify the use of this battery pack.

KEY BUYING POINTS

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 2 rack spaces (2U)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty
- NOTE: LIMIT OF 1 BP24V28-2U PER UPS, SEE BP24V70-3U FOR MULTI-PACK COMPATIBILITY

TYPICAL APPLICATIONS

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

OPTIONS & ACCESSORIES

- Tower Stands: [2-9USTAND](#)
- 2-Post Mounting Kit: [2POSTRMKITWM](#)
- Extended warranties: 3 Year [WEXT3-BP24V](#), 5 Year [WEXT5-BP24V](#)

PACKAGE INCLUDES

- BP24V28-2U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

COMPLETE SPECIFICATIONS

BATTERY

DC system voltage:	24V DC
Typical battery lifespan:	4-6 years typical (North America)
Connects to UPS via:	Attached cable with red/black 75 amp male DC connector

PHYSICAL

Shipping weight (lbs):	68
Shipping weight (kg):	30.8
Unit weight (lbs):	56.5
Unit weight (kg):	25.6
Unit Dimensions (HWD/in):	3.5 x 17.5 x 14
Unit Dimensions (HWD/cm):	8.9 x 44.5 x 35.6
Shipping Dimensions (HWD/in):	6.75 x 23.5 x 18.25
Shipping Dimensions (HWD/cm):	17.1 x 59.7 x 46.4
Material of construction:	Steel
Form factors supported:	2U rackmount housing

CERTIFICATIONS

Certifications:	CE
------------------------	----

WARRANTY

Optional coverage:	3 year, 5 year, next day and on-site warranty coverage available
Product warranty:	2 year product warranty

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2006 Tripp Lite. All Rights Reserved.