PHYSICAL INFRASTRUCTURE SYSTEMS

В. Copper Systems

> C. Fiber

Optic

Systems



Punchdown Consolidation Point Enclosures

- UL 2043 approved for use in air-handling spaces
- · Mount to wall, above ceiling, and/or below floor

• Meet ANSI/TIA-568-C.2 standard







GPB24-X **WMCPE**

All product color is black.





P110B100-X




Image reflects standard density punchdown base.

Wireless

Outlets

Cabling

GPB144-X

Н. Media Distribution

Ι. **Physical** Infrastructure Management

J. Overhead & Underfloor Routing

Surface Raceway

L. Cabinets, Racks & Cable Management

Grounding 8 Bonding

N. Industrial

0. Labeling & Identification

P. Cable Management Accessories

> 0. Index

(I) STEP PanZone® Wall Mount Consolidation Point Enclosures

- Can be directly mounted to a wall or recessed into a wall
- Include grommet edging, labels, and Tak-Ty® Hook & Loop Cable Ties
- Accommodate up to four 100-pair punchdown bases or optional patch panel bracket (PZBPPB) can be used to accommodate up to 2 RU of standard 19" patch panels
- Conduit knockouts of 1 3/4" 2" are available on top and bottom; conduit knockouts of 1 1/2" are available on the sides
- · Option of flat cover or hinged lockable door (each sold separately)









Std. Std. Pkg. Ctn. Part Number **Part Description** Qty. Qty. PanZone® Wall Mount Consolidation Point Enclosure PZB4 Enclosure, door not included; select PZB4-HC or PZB4FC. Dimensions: 25.00"H x 14.50"W x 4.65"D (635.0mm x 368.3mm x 118.1mm). PZB4-HC Hinged door to be used with PanZone® Enclosure (PZB4) when recessed in a wall. Reversible door can hinge from either side and includes lock with tab release. PZB4-FC Flat cover to be used with PanZone® Enclosure (PZB4) when mounting to wall. PanZone® Enclosure Bracket

PZBPPB Patch panel bracket accommodates up to 2 RU of standard 19" 10 patch panels. Includes one pair of brackets.

One rack space = 1.75" (44.45mm).

10

10

10