

Film, Metallized Polypropylene, Safety, R41, 2200 pF, 20%, 1,000 V, 300 V, 110C, Lead Spacing = 10mm



| General Information | |
|---------------------|------------------------------|
| Dielectric: | Metallized Polypropylene |
| Style: | Radial |
| Series: | R41 |
| Features: | Pulse |
| RoHS: | Yes |
| Lead: | Cut |
| Approvals: | AEC-Q200, ENEC, UL, cUL, CQC |
| AEC-Q200: | Yes |

| Dimensions | |
|------------|-----------------|
| L | 13mm +0.2mm |
| H | 9mm +0.1mm |
| T | 4mm +0.2mm |
| S | 10mm +/-0.4mm |
| LL | 4mm +2mm |
| F | 0.6mm +/-0.05mm |

| Specifications | |
|------------------------|-----------|
| Capacitance: | 2200 pF |
| Capacitance Tolerance: | 20% |
| Voltage DC: | 1000 VDC |
| Voltage AC: | 300 VAC |
| Temperature Range: | -40/+110C |
| Rated Temperature: | 110C |
| Dissipation Factor: | 0.3% 1kHz |
| Insulation Resistance: | 100 GOhms |
| Max dVdt: | 800 V |
| Safety Class: | Y2 |

| Packaging Specifications | |
|--------------------------|------|
| Packaging: | Bulk |
| Packaging Quantity: | 2000 |