BP24V28-2U

External Battery Pack for UPS Systems



Model #: BP24V28-2U

- Extends runtime of select compatible Tripp Lite UPS Systems with 24VDC external battery connector
- Simple installation; 2U rackmount, tower and stack adaptable
- 2-year warranty

DESCRIPTION

BP24V28-2U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 2 rack spaces (2U). Includes heavy gauge cabling with high current DC connector for simple installation.

Compatible UPS Systems - SU1000RTXL2Ua, SMART750RMXL2U, and other Tripp Lite UPS systems that specify the use of this battery pack.

KEY BUYING POINTS

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 2 rack spaces (2U)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty
- NOTE: LIMIT OF 1 BP24V28-2U PER UPS, SEE BP24V70-3U FOR MULTI-PACK COMPATIBILITY

TYPICAL APPLICATIONS

Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time
of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer
battery runtime is desired.

OPTIONS & ACCESSORIES

Tower Stands: <u>2-9USTAND</u>

2-Post Mounting Kit: <u>2POSTRMKITWM</u>

• Extended warranties: 3 Year WEXT3-BP24V, 5 Year WEXT5-BP24V

PACKAGE INCLUDES

- BP24V28-2U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

COMPLETE SPECIFICATIONS

BATTERY

Connects to UPS via: Attached cable with red/black 75 amp male DC connector

DC system voltage: 24V DC

Typical battery lifespan: 4-6 years typical (North America)

PHYSICAL

Shipping weight (lbs): 68
Shipping weight (kg): 30.8
Unit weight (lbs): 56.5

Unit weight (kg): 25.6

Unit Dimensions (HWD/in): $3.5 \times 17.5 \times 14$ Unit Dimensions (HWD/cm): $8.9 \times 44.5 \times 35.6$ Shipping Dimensions (HWD/in): $6.75 \times 23.5 \times 18.25$ Shipping Dimensions (HWD/cm): $17.1 \times 59.7 \times 46.4$

Material of construction: Steel

Form factors supported: 2U rackmount housing

CERTIFICATIONS

Certifications: CE

WARRANTY

Product warranty: 2 year product warranty

Optional coverage: 3 year, 5 year, next day and on-site warranty coverage available

The policy of Tripp Lite is one of continuous improvement.

Specifications are subject to change without notice.

Therefore, your product may vary slightly from what is currently listed.



Tripp Lite World Headquarters 1111 W. 35th Street Chicago, IL 60609 USA

> Customer Support (773) 869-1234

© 2007 Tripp Lite. All Rights Reserved.