


ME 22,5 OT-MKDSO RD

Order No.: 2853365

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2853365>

Housing upper part, for printed circuit terminal block connection

Commercial data

GTIN (EAN)	 4 017918 437060
sales group	F050
Pack	100 pcs.
Customs tariff	85472000

Product notesWEEE/RoHS-compliant since:
01/01/2003

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Certificates / Approvals

Certification

CUL, UL

Accessories		
Item	Designation	Description
Assembly		
1909236	FKCT 2,5/ 4-ST	Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Connection method: Spring-cage conn., Color: Green
2907172	ME 22,5 OT-MKDSO GN	Housing upper part, for printed circuit terminal block connection
2907143	ME B-22,5 MKDSO GN	Filler plugs, for unoccupied terminal points
2907156	ME B-22,5 MSTBO GN	Filler plugs, for unoccupied terminal points
2854173	ME B-KA	Terminal cover, 1 strip covers up to 12 terminal points, for ME-BUS terminal opening, (male side)
2935959	ME B-SA/NS 35	Terminal cover, 1 strip covers up to 12 terminal points, for ME-BUS male side, (female side)
2908760	ME DH27 NS 35	Spacers, for protection of the input or output contacts for DIN rail NS 35, width [B] 27 mm
2909895	ME DH36 NS 35	Spacers, for protection of the input or output contacts for DIN rail NS 35, width [B] 36 mm
2853899	ME-SAS	Shield connection clamp for printed circuit terminal block
1707234	MKDSO 2,5/ 4-L	PC terminal block, Nominal current: 24 A, Nom. voltage: 400 V, Pitch: 5 mm, Number of positions: 4, Connection method: Screw connection, Mounting: Soldering, Conductor/PCB connection direction: 0 °, Color: green, Article with lateral pin exit
1707247	MKDSO 2,5/ 4-R	PC terminal block, Nominal current: 24 A, Nom. voltage: 400 V, Pitch: 5 mm, Number of positions: 4, Connection method: Screw connection, Mounting: Soldering, Conductor/PCB connection direction: 0 °, Color: green, Article with lateral pin exit
1861060	MSTBO 2,5/ 4-G1L	Header, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Assembly: Soldering, Article with lateral pin exit
1861073	MSTBO 2,5/ 4-G1R	Header, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Assembly: Soldering, Article with lateral pin exit
1779851	MSTBT 2,5/ 4-ST	Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Connection method: Screw connection, Color: Green
Plug/Adapter		
1893203	MCVR 1,5/ 5-ST-3,81 AU	Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 5, Pitch: 3.81 mm, Connection method: Screw connection, Color: Green
1893216	MCVR 1,5/10-ST-3,81 AU	Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 10, Pitch: 3.81 mm, Connection method: Screw connection, Color: Green

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;