
KEMET Part Number: ALS30A222MF400

(A331PM222M400A)



Capacitor, aluminum, 2200 uF, +/-20% Tol, -40/+85C, 400V@85C



Dimensions (mm)			
Symbol	Dimension	Tolerance	
D	66	+/-1	
L	105	+/-2	
S	28.5	+/-0.5	
Т	5.5	+/-0.5	
F	13	+/-0.5	
G	10	nom	
M	5		

Notes:

-Dimensions D and L include sleeving

General Information	
Manufacturer:	KEMET
Part Type Description:	Computer Grade Aluminum Electrolytic
Style:	Computer Grade
Lead Type:	Oval Threaded Inserts- M5
Mounting Type:	Clip- V10/UTE2738

Specifications		
Capacitance:	2200 uF	
Tolerance:	+/-20%	
Rated Temperature:	85C	
Voltage @ rated temp:	400V	
VDC Surge:	440WVDC	
Transient Voltage:	520V	
Life @ rated temp:	19000 h	
RoHS:	Yes	
Low Z/ESR:	Yes	
Temperature Range:	-40/+85C	
ESR at 100Hz @ room temp:	62 mOhm	
ESR at 120Hz @ room temp:	58 mOhm	
ESR at 100kHz @ room temp:	41 mOhm	
Leakage Current:	5.28 mA	
Leakage Condition:	5min/20c	
Impedance @ 10kHz:	44 mOhm	
Impedance @ 100kHz:	43 mOhm	
Ripple 100Hz @ rated temp:	11.2 A	
Ripple 10kHz @ rated temp:	18.8 A	

Packaging Specifications		
Package Kind:	Bulk	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

