

## **Product Change Notification**

PCN Number: QC132701 Notification Date: August 26, 2013

Product I dentification:  AT42QT1481-AU  AT42QT1481-AUR  Reason for Change:	Title: Revision Change for AT42QT1481					
Reason for Change:   Material / Composition   Manufacturing Location   Processing / Manufacturing   Quality / Reliability   Design / Firmware   Logistics   Datasheet   Other:    Change Description: This notification is to advice our customers that Atmel will introduce new revisions of the QTouch controller products listed above. The new revisions are package and pin compatible to the existing revisions. They are introduced in order to enhance the product. Actual devices changes are minimal, but for your reference they are listed here together with enhancements that are a pure superset of existing functions.  Changes   FMEA   Enhancement; failure flag was set during device initialization.   Bug fix; Added a specific test of the Vref pin to the FMEA check to ensure the flag is set if the pin is open.   Bug fix: An FMEA test could incorrectly fail on some devices leading to the device locking up.   Frequency Hopping - added mode which allows quicker setup.   Noise Immunity Improvement - when some buttons are disabled and X7R caps are being used.  Identification Method to Distinguish Change:   Devices are marked with AT42QT1481-AU(R) 70 where 70 indicate Revision 7.0.   Qualification   Will be available (mm/dd/yr):   Not Applicable   Samples:   Available   Will be available (mm/dd/yr):   Not Applicable   Quantifiable Impact on Quality & Reliability:   Improved Quality and Reliability						
Reason for Change:	AT42QT1481-AU					
Processing / Manufacturing   Quality / Reliability   Design / Firmware   Logistics   Other:	AT42QT1481-AUR					
Design / Firmware	Reason for Change	:	mposition	☐ Manuf	acturing Location	
Change Description: This notification is to advice our customers that Atmel will introduce new revisions of the QTouch controller products listed above. The new revisions are package and pin compatible to the existing revisions. They are introduced in order to enhance the product. Actual devices changes are minimal, but for your reference they are listed here together with enhancements that are a pure superset of existing functions.  Changes  FMEA  Enhancement; failure flag was set during device initialization. Bug fix; Added a specific test of the Vref pin to the FMEA check to ensure the flag is set if the pin is open. Bug fix; Changed the IO pin drive to ensure the SMP pin in the FMEA test will show an error if the IO pin is open. Bug fix: An FMEA test could incorrectly fail on some devices leading to the device locking up. Frequency Hopping - added mode which allows quicker setup. Noise Immunity Improvement - when some buttons are disabled and X7R caps are being used.  Identification Method to Distinguish Change:  Devices are marked with AT42QT1481-AU(R) 70 where 70 indicate Revision 7.0.  Qualification Will be available (mm/dd/yr): Applicable  Samples: Wavailable Will be available (mm/dd/yr): Applicable  Quantifiable Impact on Quality & Reliability: Improved Quality and Reliability		☐ Processing /	Manufacturing	□ Quality	y / Reliability	
Change Description: This notification is to advice our customers that Atmel will introduce new revisions of the QTouch controller products listed above. The new revisions are package and pin compatible to the existing revisions. They are introduced in order to enhance the product. Actual devices changes are minimal, but for your reference they are listed here together with enhancements that are a pure superset of existing functions.  Changes  • FMEA  • Enhancement; failure flag was set during device initialization. • Bug fix; Added a specific test of the Vref pin to the FMEA check to ensure the flag is set if the pin is open. • Bug fix; Changed the IO pin drive to ensure the SMP pin in the FMEA test will show an error if the IO pin is open. • Bug fix: An FMEA test could incorrectly fail on some devices leading to the device locking up. • Frequency Hopping - added mode which allows quicker setup. • Noise Immunity Improvement - when some buttons are disabled and X7R caps are being used.  Identification Method to Distinguish Change:  Devices are marked with AT42QT1481-AU(R) 70 where 70 indicate Revision 7.0.  Qualification  Data:  Mill be available (mm/dd/yr):  Applicable  Samples:  Wavailable  Will be available (mm/dd/yr):  Applicable  Quantifiable Impact on Quality & Reliability:  Improved Quality and Reliability		☐ Design / Firn	nware	Logist	ics	
Change Description: This notification is to advice our customers that Atmel will introduce new revisions of the QTouch controller products listed above. The new revisions are package and pin compatible to the existing revisions. They are introduced in order to enhance the product. Actual devices changes are minimal, but for your reference they are listed here together with enhancements that are a pure superset of existing functions.  Changes  Enhancement; failure flag was set during device initialization.  Bug fix; Added a specific test of the Vref pin to the FMEA check to ensure the flag is set if the pin is open.  Bug fix; Changed the IO pin drive to ensure the SMP pin in the FMEA test will show an error if the IO pin is open.  Bug fix: An FMEA test could incorrectly fail on some devices leading to the device locking up.  Frequency Hopping - added mode which allows quicker setup.  Noise Immunity Improvement - when some buttons are disabled and X7R caps are being used.  Identification Method to Distinguish Change:  Devices are marked with AT42QT1481-AU(R) 70 where 70 indicate Revision 7.0.  Qualification  Will be available (mm/dd/yr):  Applicable  Samples:  Wavailable Will be available (mm/dd/yr):  Applicable  Quantifiable Impact on Quality & Reliability:  Improved Quality and Reliability		Datasheet		_		
Devices are marked with AT42QT1481-AU(R) 70 where 70 indicate Revision 7.0.  Qualification Data: Will be available (mm/dd/yr): Applicable  Samples: Will be available (mm/dd/yr): Not Applicable  Quantifiable Impact on Quality & Reliability:  Improved Quality and Reliability	This notification is to advice our customers that Atmel will introduce new revisions of the QTouch controller products listed above. The new revisions are package and pin compatible to the existing revisions. They are introduced in order to enhance the product. Actual devices changes are minimal, but for your reference they are listed here together with enhancements that are a pure superset of existing functions.  Changes  FMEA  Enhancement; failure flag was set during device initialization.  Bug fix; Added a specific test of the Vref pin to the FMEA check to ensure the flag is set if the pin is open.  Bug fix; Changed the IO pin drive to ensure the SMP pin in the FMEA test will show an error if the IO pin is open  Bug fix: An FMEA test could incorrectly fail on some devices leading to the device locking up.  Frequency Hopping - added mode which allows quicker setup.					
Qualification Data:       □ Will be available (mm/dd/yr): Applicable         Samples:       □ Available       □ Will be available (mm/dd/yr): □ Not Applicable         Quantifiable Impact on Quality & Reliability:         Improved Quality and Reliability	Identification Method to Distinguish Change:					
Data:       Applicable         Samples:       Available       Will be available (mm/dd/yr):       Not Applicable         Quantifiable Impact on Quality & Reliability:       Improved Quality and Reliability	Devices are marked with AT42QT1481-AU(R) 70 where 70 indicate Revision 7.0.					
Quantifiable Impact on Quality & Reliability: Improved Quality and Reliability			☐ Will be available (mm/	/dd/yr):	_	
Improved Quality and Reliability	Samples:		☐ Will be available (mm/	/dd/yr):		
	Quantifiable Impact on Quality & Reliability:					
Proposed First Ship Date*: November 23, 2013	Improved Quality and Reliability					
*The Proposed First Ship Date is the forecasted date that a customer may expect to receive changed product. This is determined by the estimated date of inventory depletion on the PCN issue date. This may be affected by fluctuations in supply and demand. Consequently, although customers should be prepared to receive changed product on this date, Atmel will continue to ship pre-changed product until a time in which inventory has been depleted. This may result in pre-changed product being shipped to customers after this forecasted date.						

ATMEL 1560 Parkway, Solent Business Park, Whiteley, Fareham, Hampshire, PO15 7AG · United Kingdom

**Atmel Contact:** Please contact your Atmel Sales Representative or Distributor for additional information (when replying via e-mail please include the PCN number in subject line).

Information provided herein is in connection with Atmel products and this information is provided "AS IS". Atmel assumes no responsibility for any errors that may appear in this document. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Atmel's Terms and Conditions of Sale for such products, Atmel assumes no liability whatsoever, and Atmel disclaims any express or implied warranty, including liability or warranties relating to fitness for a particular purpose, merchantability, or non-infringement of any patent, copyright or other intellectual property right. Atmel products are not intended for use in a product or system intended to support or sustain life which, if it fails, can be reasonably expected to result in significant personal injury. Atmel may make changes to specifications and product descriptions at any time, without notice.

<b>CUSTOMER ACKNOWLEDGEMENT OF RECEIPT:</b> Atmel requests you acknowledge receipt of				
this PCN. Please complete and email to <a href="mailto:pcnadm@atmel.com">pcnadm@atmel.com</a> and the Atmel Contact listed				
above. In your acknowledgement, you can grant approval or request additional information.				
Atmel will deem this change accepted unless specific conditions of acceptance are				
provided in writing within 30 days from the date of this notice.				
To be completed by customer:				
Approved				
Rejected (Please state reason for rejection):				
Company:				
Name:				
Title:				
Date:				
Email				
Address:				
Location:				
Comments:				