



**Have a Question?**  
 Chat with a Product  
 Information Specialist

What can we help you find?

[Products](#) [Industries](#) [Resources](#) [About TE](#) [My Account](#) [Innovation](#) [Support Center](#)

**5227726-3 Product Details**

[Share](#) [Print](#) [Email](#)



**5227726-3**

TE Internal Number: 5227726-3

**Active**

[View 3D PDF](#)

**BNC RF Connectors**

Always EU RoHS/ELV Compliant (Statement of Compliance)

**Product Highlights:**

- Connector - RF
- Jack
- Connector Style = Jack
- Applies To Wire/Cable
- Coaxial Cable Termination Type = Solder

[View all Features](#)

**Quick Links**

- [Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

**Documentation & Additional Information**

**Product Drawings:**

- [SOLDER JACK, ISOLATED, 50 OHM, BNC \(PDF, English\)](#)

**Catalog Pages/Data Sheets:**

- [BNC Connectors \(PDF, English\)](#)

**Product Specifications:**

- None Available

**Application Specifications:**

- None Available

**Instruction Sheets:**

- None Available

**CAD Files:** ([CAD Format & Compression Information](#))

- [2D Drawing \(DXF, Version A\)](#)
- [3D Model \(IGES, Version A\)](#)
- [3D Model \(STEP, Version A\)](#)

[List all Documents](#)

**Related Products:**

- [Tooling](#)

**Product Features (Please use the Product Drawing for all design activity)**

**Product Type Features:**

- **Product Type** = Connector - RF
- **Gender** = Jack
- **Grade** = Commercial
- **Sealed** = No
- **Isolated** = Yes
- **Dielectric Material** = VALOX
- **Color** = White
- **Isolated Component** = Bulkhead
- **Solder Terminal** = Without

**Mechanical Attachment:**

- **Surface Mountable** = No
- **Hardware Included** = No
- **Panel Mount Retention** = With
- **Panel Mount Retention Type** = Bulkhead
- **Panel Attachment Style** = Front Mount

**Electrical Characteristics:**

- **Connector Impedance (Ω)** = 50

**Termination Features:**

- **Coaxial Cable Termination Type** = Solder

**Body Features:**

- **Body Style** = Straight
- **Body Plating** = Nickel
- **Body Insulation** = Without
- **Polarized** = No
- **Flange and Thread Material** = VALOX
- **Flange and Thread Material Color** = Black

**Contact Features:**

- **Center Contact Material** = Phosphor Bronze
- **Center Contact Plating** = Gold

**Housing Features:**

- **Connector Style** = Jack

**Configuration Features:**

- **Number of Ports** = 1

**Industry Standards:**

- **Government/Industry Qualification** = No
- **RoHS/ELV Compliance** = RoHS compliant, ELV compliant
- **Lead Free Solder Processes** = Not relevant for lead free process
- **RoHS/ELV Compliance History** = Always was RoHS compliant

**Conditions for Usage:**

- **Applies To** = Wire/Cable



**Other:**

- **Brand** = AMP

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AJ	16	A1	REVISED PER ECO-11-005030	11MAR11	RK HMR

1. FOR USE IN PANELS UP TO 6.35 [.250] MAXIMUM THICK.



SUGGESTED PANEL CUTOUT  
SCALE 4:1

9-414815-0	1-329492-1	227529-3	5227726-3
9-414815-0	1-329492-1	227529-2	5227726-2
9-414815-0	1-329492-1	227529-1	5227726-1
③ JAM NUT QTY=1	② LOCKWASHER QTY=1	① JACK ASSY QTY=1	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L. VARELA - DOCK5 21APR2005	TE Connectivity	
DIMENSIONS: mm [INCHES]		CHK J. HAVENER 21APR2005	NAME SOLDER JACK, ISOLATED, 50 OHM, BNC	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD J. LIPPERT 21APR2005	PRODUCT SPEC -	
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		APPLICATION SPEC -	SIZE A2	CAGE CODE 00779
MATERIAL -		FINISH -	WEIGHT .290 OZ EACH	DRAWING NO C=5227726
CUSTOMER DRAWING			SCALE 8:1	SHEET 1 of 1
			RESTRICTED TO -	REV A1