



**CONNECTORS**

**SMART CARD CONNECTORS**



✓ Active

TE CONNECTIVITY (TE)

## SIM/SAM RECPT, 6 POS, SMT

Smart Card | SIM Connectors , SIMM

5145299-1

TE Internal Number: 5145299-1

EU RoHS Compliant

EU ELV Compliant

**Accepts Card Thickness** .76 mm [ .03 in ]

**Product Type** Connector

**Number of Positions** 6

**Cable** Without

**Cable Type** Non Cable

[↓ PRODUCT DRAWING](#)  
English

[↓ 3D PDF](#)

### DOCUMENTATION

Product Drawings

**SIM/SAM CONNECTOR WITH LID, 8 POSN OR 6 POSN WITH SWITCH, SURFACE MOUNT**

PDF

**English**

CAD Files

**Customer View Model**

2D\_DXF.ZIP

**English**

**3D PDF**

PDF

**3D**

## Customer View Model

3D\_IGS.ZIP

English

## Customer View Model

3D\_STP.ZIP

English

---

Product Specifications

Application Specification

## Subscriber Identity Module/Security Access Module (SIM/SAM) SMT (Surface Mount Technology) Card Connectors

PDF

English

Product Specification

## Connector, SIM/SAM

PDF

English

---

## FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

---

### Product Type Features

**Switch Style** Unsealed

**Product Type** Connector

**Cable Type** Non Cable

**Card Scoop** With

**Profile** Standard

**Card Guide Slots** With

**Card Type** SIM/SAM

**Strain Relief** Without

---

### Configuration Features

**Cover** With

**Number of Positions** 6

**Cable** Without

**Cable Mounting Style** Non Cable

**Number of Signal Contacts** 6

**Card Detection Switch Position** No

**Card Detection Switch** With

---

### Contact Features

**Solder Tail Contact Plating Material** Tin over Nickel

**Contact Mating Area Plating Material** Gold

**Number of Switch Contacts** 2

**Contact Base Material** Phosphor Bronze

---

### Termination Features

**Termination Type** IDC

---

Mechanical Attachment

**PCB Mounting Style** Surface Mount

---

Housing Features

**Housing Material** High Temperature Thermoplastic

**Housing Color** Black

---

Dimensions

**Accepts Card Thickness** .76 mm [ .03 in ]

**Height above PC Board (mm)** 1.55, 4.05

**Height above PC Board (in)** .059, .159

---

Operation/Application

**Durability Rating (Cycles)** 10000

---

Packaging Features

**Packaging Quantity** 500

**Packaging Method** Carton

---

Other

**Comment** Designed to accept GSM 11.11 SIM (Subscriber Identity Module) and SAM (Security Access Module) Integrated Circuit Cards. Has Stainless Steel Locking Disk., Has Stainless Steel Locking Disk

---

## PRODUCT COMPLIANCE



Statement of Compliance

**Statement of Compliance**

PDF

---