## **IMPEDANCE MATCHING PADS**

SMA (50  $\Omega$ )/Type F (75  $\Omega$ ), DC - 3 GHz, 5.7 dB

## **SPECIFICATIONS:**

RoHS Compliant

Models: 9080-50/75, 9076-50/75, 9088-50/75, 9079-50/75


Frequency Range	DC - 3 GH
Attenuation	5.7 ±0.5 dl
VSWR	1.25:1 Max
Input Power	2 Watts Avg @ +25°C
	Derated Linearly to 0.5 Watts @ +125°C
Peak Power	250 Watts Max
Mechanical:	(5uSec Pulse, .05% Duty Cycle)
SMA Connectors Mates with MILSTD-348	Passivated Stainless Stee
Type F Connectors	Nickel Plated Bras
Housings	Passivated Stainless Stee
Center Contacts	Gold Plated Beryllium Coppe




Model Number: 9080-50/75 SMA Male / Type F Male

> 1.29 ±.05 [32.8 ±1.3]


Model Number: 9076-50/75 SMA Male / Type F Female



Model Number: 9079-50/75 SMA Female / Type F Male



Model Number: 9088-50/75 SMA Female / Type F Female



Note: Dimensions in Brackets are Expressed in Millimeters and are for Reference Only.

9080-50/75: REV E

