

This website stores cookies on your computer. These cookies are used to collect information about how you interact with our website and allow us to remember you. We use this information in order to improve and customize your browsing experience and for analytics and metrics about our visitors both on this website and other media. To find out more about the cookies we use, see our Privacy Policy.

If you decline, your information won't be tracked when you visit this website. A single cookie will be used in your browser to remember your preference not to be tracked.

- Feature a large diameter, low-profile head and knurled shank.
- Offers highest all around strength.




Type	Threads	Standard Material	Standard Finish
ALLS / HNS	Knurled, 18 per 1/16" Ø11 Metric, 18 per 1/16" Ø11.28	Low Carbon Steel	Boyd's Compound Zinc Yellow Plus Lubricant
ALLS / HNS	Knurled, 18 per 1/16" Ø11 Metric, 18 per 1/16" Ø11.28	Stainless Steel	Passivated and/or tested per ASTM A308
ALLS / HNS	Knurled, 18 per 1/16" Ø11 Metric, 18 per 1/16" Ø11.28	Aluminum	No finish
ALLS / HNS	Knurled, 18 per 1/16" Ø11 Metric, 18 per 1/16" Ø11.28	Brass	No finish

Specifications

Thread Size #10-32

Grip Range .130 - .225 in

B ± .015 .415 in



C Nom. .030 in

øD Max. .296 in

M Ref. .315 in

Hole Size in Sheet + 0.006 - 0.000 .297 in

Fastening Installed

Thread Specification	2B per ASME B1.1
Standard Material	Low Carbon Steel
Standard Finish	RoHS Compliant Zinc Yellow Plus Lubricant
CAD Supplier	PennEngineering® (Atlas®)