

[IDEC](#)

- [HOME](#)
- Industrial Components
- [Switches & Pilot Devices](#)
- [TWND 30mm Series](#)
- ASD33L20NU

ASD33L20NU 30mm 3pos Lvr 2way-Spr 2NO

•



[Add to Cart](#)

Key Features

- Diecast zinc mounting threads
- Heavy-duty design for all type of harsh environments
- IP20 finger-safe contact block
- Ease of installation and wiring
- UL Listed, CSA Certified, TUV Approved, and CE Marked



- [Specifications](#)
- [Literature](#)
- [Downloads](#)
-
-

Operation Type	Spring return
Mounting Hole Size	30mm
Shape	Lever Operator
Number of Positions	3
Contact Configuration	2NO
Terminal Type	Screw (M3.5)
Ingress Protection Rating	IP65
Operator Position Angle	45 deg.

Product Families

- [Automation](#)
- [Hazardous Location](#)
- [Industrial Components](#)
- [LED Lighting & Signaling](#)
- [Machine Safety](#)
- [Sensing](#)

- [Sign In/Register](#)
-

- [HOME](#) [PRODUCTS](#) [SUPPORT](#) [ABOUT US](#) [NEWS](#) [CONTACT](#)
- [Privacy Policy](#)
- [Site Map](#)
- [Contact Us](#)