

\$ 4.99 - Standard Global Shipping

[Home](#) > [Products](#) > [RF & Wireless Control](#) > [RF Diode](#) > [RF Mixer and Detector Schottky Diode](#) > [BAT62-02V](#)

# BAT62-02V

- Overview**
- Documents
- Order
- Simulation
- Support

## Description:

Silicon Schottky Diodes

## Summary of Features:

- Low barrier diode for detectors up to GHz frequencies
- Pb-free (RoHS compliant) package

## Target Applications:

- Wireless Communications
- Satellite Receivers
- Base Stations
- High Speed Data Networks
- RFID

Buy online

Designers who used this product also designed with

In order to optimize your browsing experience Infineon uses cookies. You agree to the usage of cookies when you continue browsing this site. For more information regarding cookies and the processing of your personal data please read our [Privacy Policy](#).

OK

[BAT60B](#) |   
Medium Power IF max  $\geq$  500mA

[BGA420](#) |   
General Purpose LNAs

[SPB08P06P G](#) |   
12V-250V P-Channel Power MOSFET

[BSP75N](#) |   
Automotive Smart Low-Side Switch | HITFET™

[BFP420F](#) |   
Low-Noise Si Transistors up to 5 GHz

## Documents

+ Expand all

+ [Application Notes](#)

+ [Product Qualification Report](#)

+ [Material Content Sheet](#) Info

## Order

Sales Product Name	BAT62-02V
OPN	BAT6202VH6327XTSA1
Product Status	active and preferred
Package name	<a href="#">SC79</a>
Order online	
Completely lead free	yes
Halogen free	yes
RoHS compliant	yes
Packing Size	3000
Packing Type	TAPE & REEL
Moisture Level	1
Moisture Packing	NON DRY

## Simulation

+ [Simulation Models](#)

## Support

Live Chat Online  
在线支持

Technical Assistance Center  
技术支持中心 (TAC)

Call us Toll Free  
免费热线联系我们

+ [Find an answer to your question](#)

+ [Technical Assistance Center \(TAC\)](#)

+ [Support forum](#)

Follow us