



Electrical Commercial and Industrial

- Products
- Documentation & Literature
- News & Tradeshows
- Support

United States > All 3M Products > Market Segments > Electronics, Electrical, and Communications > Electrical Products > Electrical Commercial and Industrial > Products > Electrical Commercial & Industrial Products Catalog > Heat Shrink > Medium/Heavy Wall > 3M™ Heat Shrink ITCSN > 3M™ Heat Shrink Heavy-Wall Cable Sleeve for 1 kV ITCSN-0800-12-Bulk, 8-1/0 AWG, Expanded/Recovered I.D. 0.80/0.20 in, 12 in Length, 100 per case

[Find An Account Rep](#)

[Where To Buy \(Find A Distributor\)](#)

[Contact Us](#)

3M™ Heat Shrink Heavy-Wall Cable Sleeve for 1 kV ITCSN-0800-12-Bulk, 8-1/0 AWG, Expanded/Recovered I.D. 0.80/0.20 in, 12 in Length, 100 per case

3M ID 80008007215 UPC# 00054007089674 3M Product Number ITCSN-0800-12"-Black-100 Pcs

[Print](#)

[Share](#)



3M™ Heat Shrinkable Cable Sleeves ITCSN provide reliable performance for electrical splices, connections and terminations, as well as mechanical and environmental protection. This cable sleeve comes in a length of 12 inch.

[Buy Online at Shop3M.com](#)

Need Help?

Questions? We can help
[Contact Us](#)

- Overview
- Documentation

Specifications

Color	Black
Expanded Inner Diameter	0.80 Inch
Expanded Inner Diameter (metric)	20.3 mm
Length	9 Inch
Length (metric)	229 Millimetre
Material	Polyolefin
Operating Temperature Range (Celsius)	-55 Degrees C to -100 Degrees C
Operating Temperature Range (Fahrenheit)	-67 to 230 Degree Fahrenheit
Product Type	Splice
Recovered Inner Diameter	0.20 Inch
Recovered Inner Diameter (metric)	5.1 mm
Shrink Ratio	3:1
Specifications	UL 486D*
Splice Type	Heat Shrink
Voltage Rating	UL Rated to 600 V, Can be used up to 1 kV

