

[Products](#) [Contact Us](#) [Catalogs](#) [Sample Program](#) [Free CAD](#)

[Home](#) [Caps, Plugs & Masking](#) [Push Fit Caps](#) [Masking Caps](#) [Masking Straight Caps](#)



## Masking Straight Cap & Plug: .172 in (4.4 mm) Cap ID, 180 °C (356 °F) Max. Temp.,.500 in (12.7 mm) Height

● In Stock

Item Code: SC017205B

Black EPDM Masking Straight Cap & Plug has a .172 in (4.4 mm) I.D. and Inside Height of .500 in (12.7 mm) to mask threaded or non-threaded components during finishing processes.



Description	Quantity	Options																	
<table border="0"> <tr> <td>Cap Inside Diameter</td> <td>: .172 in (4.4 mm)</td> <td><input type="text" value="1"/></td> </tr> <tr> <td>Compatible Thread Sizes (All)</td> <td>: #10-24</td> <td rowspan="5"> <div style="background-color: red; color: white; padding: 5px; text-align: center; margin-bottom: 5px;"><b>Add to Cart</b></div> <div style="background-color: #ccc; padding: 5px; text-align: center; margin-bottom: 5px;">Request CAD</div> <div style="background-color: #ccc; padding: 5px; text-align: center; margin-bottom: 5px;">Free Sample</div> <div style="background-color: #ccc; padding: 5px; text-align: center;">Request Quote</div> </td> </tr> <tr> <td>Inside Height</td> <td>: .500 in (12.7 mm)</td> </tr> <tr> <td>Fitting Style</td> <td>: Push Fit</td> </tr> <tr> <td>Special Features (All)</td> <td>: Reusable</td> </tr> <tr> <td>Temperature Range</td> <td>: 180 °C (356 °F)</td> </tr> <tr> <td>Hardness</td> <td>: 55 ± 5 (Shore A)</td> <td></td> </tr> </table>	Cap Inside Diameter	: .172 in (4.4 mm)	<input type="text" value="1"/>	Compatible Thread Sizes (All)	: #10-24	<div style="background-color: red; color: white; padding: 5px; text-align: center; margin-bottom: 5px;"><b>Add to Cart</b></div> <div style="background-color: #ccc; padding: 5px; text-align: center; margin-bottom: 5px;">Request CAD</div> <div style="background-color: #ccc; padding: 5px; text-align: center; margin-bottom: 5px;">Free Sample</div> <div style="background-color: #ccc; padding: 5px; text-align: center;">Request Quote</div>	Inside Height	: .500 in (12.7 mm)	Fitting Style	: Push Fit	Special Features (All)	: Reusable	Temperature Range	: 180 °C (356 °F)	Hardness	: 55 ± 5 (Shore A)			
Cap Inside Diameter	: .172 in (4.4 mm)	<input type="text" value="1"/>																	
Compatible Thread Sizes (All)	: #10-24	<div style="background-color: red; color: white; padding: 5px; text-align: center; margin-bottom: 5px;"><b>Add to Cart</b></div> <div style="background-color: #ccc; padding: 5px; text-align: center; margin-bottom: 5px;">Request CAD</div> <div style="background-color: #ccc; padding: 5px; text-align: center; margin-bottom: 5px;">Free Sample</div> <div style="background-color: #ccc; padding: 5px; text-align: center;">Request Quote</div>																	
Inside Height	: .500 in (12.7 mm)																		
Fitting Style	: Push Fit																		
Special Features (All)	: Reusable																		
Temperature Range	: 180 °C (356 °F)																		
Hardness	: 55 ± 5 (Shore A)																		

[Print Page](#)

### Products you might be interested in



Masking Straight Cap & Plug: .172 in (4.4 mm) Cap ID, 180 °C (356 °F) Max. Temp.,.500 in (12.7 mm) Height

**ESSENTIAL SOLUTIONS** **DELIVERED**

- Abrasives & Grinding
- Access Hardware
- Adhesives, Sealants & Tapes
- Bearings & Power Transmissions
- Caps & Plugs

- Clamps & Workholdings
- Cutting & Machining
- Extrusions & Structural Systems
- Fasteners
- Feet, Casters & Glides

- Fiber, Wire & Cable Management
- Flange Protection
- Knobs, Handles & Grips
- Material Handling
- Shop Supplies

- PCB & Electronics Hardware
- Pneumatics & Hydraulics
- Raw Materials
- Tamper Evident & Security Seals
- Tooling & Positioning Components
- Tools & Precision Instruments

**About Us**

- About Essentra Components
- About Essentra PLC
- Locations

**Customer Service**

- Contact Us
- Catalogs
- Sample Program
- Free CAD
- Careers
- Distributor Portal

**Policies**

- Privacy Policy
- Terms and Conditions of Sale
- Terms and Conditions of
- Purchase
- Environmental Policy
- Health and Safety
- Quality Statement

**Terms of Use**

- Website Terms of Use
- Cookie Policy



**ABOUT SSL CERTIFICATES**