

You are here: [Products](#) » [Heatsinks f.cool](#) » [Profile heatsinks and fluid coolers](#) » [Standard extruded heatsinks](#) » [SK 427 ...](#) » [SK 427](#)

▼ Heatsinks f.cool

- ▼ Profile heatsinks and fluid coolers
  - [Standard extruded heatsinks](#)
  - Extruded heatsinks for lock-in retaining spring
  - Extruded heatsinks for PCB mounting
  - Extruded heatsinks for DC/DC converter
  - Retaining springs for transistors
  - U-Extruded heatsinks
  - Die-cast heatsinks
  - Fin coolers
  - Fluid coolers
  - Aluminium flat-, quadrangular-, angled-, U- and T-profiles
- ▶ Heatsinks and active heatsinks for processors
- ▶ Board Level heatsinks
- ▶ Cooling aggregates
- ▶ Accessories for electronic components
- ▶ **Cases f.case**
- ▶ **Connectors f.con**

Standard extruded heatsinks


SK 427 ...

SK 427 50 AL

50,8 x 8 mm

[Data sheet](#)

[add to request](#)



Features Technical Drawing Service

<b>thermal resistance <math>R_{th}</math></b>	11 - 5.5 KW
<b>surface</b>	raw degreased aluminium
<b>height</b>	8 mm
<b>width B</b>	50.8 mm
<b>length</b>	50 mm
<b>plate thickness</b>	3 mm