

You are here: Products » Heatsinks f.cool » Profile heatsinks and fluid coolers » Standard extruded heatsinks » SK 81 ... » SK 81


- ▼ Heatsinks f.cool
  - ▼ Profile heatsinks and fluid coolers
    - Standard extruded heatsinks
    - Extruded heatsinks for lock-in retaining spring
    - Extruded heatsinks for PCB mounting
    - Extruded heatsinks for DC/DC converter
    - Retaining springs for transistors
    - U-Extruded heatsinks
    - Die-cast heatsinks
    - Fin coolers
    - Fluid coolers
    - Aluminium flat-, quadrangular-, angled-, U- and T-profiles
  - ▶ Heatsinks and active heatsinks for processors
  - ▶ Board Level heatsinks
  - ▶ Cooling aggregates
  - ▶ Accessories for electronic components
  - ▶ Cases f.case
  - ▶ Connectors f.con

Standard extruded heatsinks

SK 81 ...

SK 81 100 SA  
100 x 15 mm

Data sheet add to request



Features Technical Drawing Service

<b>thermal resistance <math>R_{th}</math></b>	3.4 - 1.9 K/W
<b>surface</b>	black anodised
<b>height</b>	15 mm
<b>width B</b>	100 mm
<b>length</b>	100 mm
<b>plate thickness</b>	4 mm